

# WALLPAPER PASTE UNIVERSAL

## WALLPAPER PASTE BASED ON HIGH QUALITY STARCH.



### PRODUCT DESCRIPTION

Wallpaper paste based on high quality starch.

### FIELD OF APPLICATION

To hang all types of wallpaper: lightweight, normal, heavy and extra heavy, special, vinyl and textile wallpapers.

### PROPERTIES

- Does not lump
- Does not stain
- Spreads easily
- Easy to correct
- Moisture resistant
- Super strong
- pH neutral
- Ready to use within 15 minutes
- Airtight packaging
- Paste stays fresh

### PREPARATION

**Working conditions:** Dab up fresh stains immediately with a damp cloth.

**Preliminary treatment:** Substrate must be clean, dry, smooth and free of dust and grease. Remove old layers of wallpaper with Bison Wallpaper Stripper. Remove loose plasterwork and fill holes with Bison Repair Kit. Walls treated with latex should be cleaned first with a mixture of water and ammonia or paint remover, then allowed to dry well. Thoroughly roughen non-absorbent walls (e.g. latex wall paint). Prepaste highly absorbent walls (e.g. board or fresh plasterwork) with diluted wallpaper paste. Clean and dry walls very well. Impurities on the wall can cause staining on wallpaper.

**Tools required:** Pasting brush, bucket, stirring stick, table to paste on. Clean

tools with water immediately after use.

### APPLICATION

**Dilute:** Dilute only with water

#### Directions for use:

Mix contents little by little with cold water while stirring firmly until paste is lump free. Stir again firmly after 15 minutes. The paste is now ready for use. Apply paste generously and evenly on wallpaper strips with a brush. Pay extra attention to the edges. Fold both ends of the strips to the middle and let paste soak in. When hanging the wallpaper, press the seams properly, if necessary with a roller. Hang wallpaper following instructions from wallpaper manufacturer. Prepared paste will keep for several days if stored in well-closed container.

**Stains/residue:** Dab up fresh stains and excess paste immediately with a clean, damp cloth.

### TECHNICAL PROPERTIES

**Moisture resistance:** Good

### TECHNICAL SPECIFICATIONS

**Base:** Starch

**Solid contents:** approx. 100 %

### SHELF LIFE

At least 24 months after date of manufacture Limited shelf life after opening Store in a dry, cool and frost-free place.