

## Препарат Rust-Oleum за сваляне на боя и лепило 0.5 л, Nr.1 Green Paint Stripper

### NR.1 GREEN PAINT STRIPPER

#### DESCRIPTION

Highly effective paint remover for all paint types and glue without methylene chloride.

#### RECOMMENDED USE

Nr. 1 Green Paint Stripper can be used for a quick removal of layers of old paint and glue. Green Paint Stripper is developed to remove all types of oil- and alkyd based paints, emulsion paints, varnish and most two-component materials from metal, mineral and wooden surfaces. Does not contain methylene chloride, NMP, acids, alkalis, biocides and conservation additives. It will not affect metal, mineral or wooden substrates.

#### TECHNICAL DATA

Density (g/cm<sup>3</sup>): 0,99  
Propellant: Dimethyl ether

#### PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as type of old coating and shape of the substrate and material losses during application.

#### SURFACE PREPARATION

Remove loose coatings as much as possible by scraping.

#### DIRECTIONS FOR USE

Can: To release possible pressure open the can carefully.  
Aerosol: Remove cover cap. Shake vigorously before use.

#### APPLICATION CONDITIONS

Temperature of air, substrate and material between 0 and 30°C and relative humidity below 85%.

#### APPLICATION & THINNING: BRUSH

Apply Green Paint Stripper thickly in an even layer with a brush (disposable brush, flat or round). Do not use synthetic brushes. Allow to stand for 10 to 15 minutes, and remove the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with a cleaner (f.e. ND 14), high pressure (steam) cleaning, fresh water and allow to dry completely before applying a coating.

#### APPLICATION & THINNING: AEROSOL

Hold the can approx. 10-20 cm from the substrate. Apply a uniform foam layer of Paint Stripper 2925; allow standing for minimal 15 minutes, and removing the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with cleaner/degreaser, fresh water or white spirit and allow drying completely before applying a coating.

#### REMARKS

Nr. 1 Green Paint Stripper may affect plastic materials like e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand.

#### SAFETY DATA

VOC level: 900 g/l  
Remarks regarding safety: Do not use in the immediate vicinity of flames, hot surfaces or welding works. No smoking. Consult Safety Data Sheet and Safety Information printed on the can.  
For the 2.5L & 0.75L: Attention! Open the can carefully to release possible pressure.

#### SHELF LIFE

1 year (can) and 2 years (aerosol) from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 30°C.



Продукт: [Препарат Rust-Oleum за сваляне на боя и лепило 0.5 л, Nr.1 Green Paint Stripper](#)

Категория: [Битова химия](#)

Марка: [Марка Rust-Oleum](#)

Тип: [Препарат Rust-Oleum](#)