

## Спрей Rust-Oleum технически противоплъзгащ 0.5 л, черен, SuperGrip Anti-Slip

### SUPERGRIP® ANTI-SLIP SPRAY

#### DESCRIPTION

This topcoat makes every surface Non-skid in a second. SuperGrip™ Anti-Slip sprays are based on a fast drying acrylic modified short oil alkyd. The coloured products are based on lead- and chromate free pigments and contain a special anti-slip additive. Should be applied on metal, concrete, ceramic and wood surfaces or properly prepared painted substrates.

#### RECOMMENDED USE

RUST-OLEUM Anti-Slip 2400 should be applied on metal, concrete, ceramic and wood surfaces or properly prepared painted substrates. Steel should be primed with 2169 or 2182. RUST-OLEUM Anti-Slip 2400 are intended for small maintenance jobs or for touch-up. RUST-OLEUM Anti-Slip 2400 should be used interior/exterior in light industrial exposures where anti slip characteristics are required.

#### DRY TIMES BY 20° C/RV 50%

Touch dry:	20 minutes
Dry to handle:	60 minutes
Dry to recoat:	after 1 hour with itself
Fully cured:	7 days

#### RECOMMENDED WET FILM THICKNESS

100 µm

#### RECOMMENDED DRY FILM THICKNESS

25 µm

#### THEORETICAL CONSUMPTION

2,5 m<sup>2</sup> per spray can at 25 µm dry

#### PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

#### SURFACE PREPARATION

Remove dirt, grease, oil, loose rust and all other surface contaminants by appropriate means. Sand intact coatings to provide a proper key for adhesion. The surface must be clean and dry during application

#### APPLICATION CONDITIONS

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 10°C.

#### APPLICATION & THINNING: AEROSOL

Remove cover cap. Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use. Hold the can approx. 25 cm from surface. Use back and forth motion keeping can parallel with surface. Ensure that can is in motion when spray button is pressed to avoid runs and sags. Apply several thin layers at a few minutes interval to achieve adequate coating thickness. After use turn can upside down and press spray button for 2 - 3 seconds to clean valve.

#### REMARKS

Not for use in wet areas such as bathrooms or on substrates which are regularly in contact with water.

#### SAFETY DATA

VOC level:	524 - 538 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

#### SHELF LIFE

3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not indirect sunlight at temperatures between 5° and 35°C.



Продукт: [Спрей Rust-Oleum технически противоплъзгащ 0.5 л, черен, SuperGrip Anti-Slip](#)

Категория: [Спрей боя](#)

Марка: [Марка Rust-Oleum](#)

Тип: [Спрей Rust-Oleum](#)