

Грунд Rust-Oleum защита от графити 10 л, Graffitishield Hydro

GRAFFITISHIELD™ HYDRO

DESCRIPTION

Water based permanent anti-graffiti coating with hydrophobic properties for mineral substrates.

RECOMMENDED USE

GraffitiShield™ HYDRO can be applied to all porous mineral surfaces, such as concrete, brickwork, and dimension stone.

TECHNICAL DATA

Density (g/cm³): 1,0
Gloss Level: Matt
Solids content in volume: 10%

DRY TIMES BY 20° C/RV 50%

Touch dry: 1 hour
Dry to handle: 1 hour
Dry to recoat: 1 hour (with itself)
Fully cured: 3 days

THEORETICAL CONSUMPTION

5 - 10 m²/l

PRACTICAL CONSUMPTION

Dependent on many factors, such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

The surface should be clean, dry, and free of dirt and grease.

DIRECTIONS FOR USE

Before use, shake up and stir well to ensure a good degree of homogeneity. Lay on two coats, with a drying interval of at least 60 minutes between coats.

APPLICATION & THINNING: AIRLESS SPRAY

Do not dilute. Nozzle 013-015. It is advisable to cover up windows and doors during application.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Do not dilute. It is advisable to cover up windows and doors during application.

CLEANING OF EQUIPMENT / SPILLS

Water.

REMARKS

Remove graffiti with GraffitiShield™ CLEANER. GraffitiShield™ HYDRO will remain fully intact once graffiti has been removed, allowing for many rounds of cleaning.

SAFETY DATA

VOC level: 66 g/l
VOC ready mix: 66 g/l
VOC category: A/i
VOC limit: 140 g/l
Remarks regarding safety: Consult the relevant product safety sheet and information on the packaging.

SHELF LIFE

1 year from production date, provided it is stored in the unopened original packaging, in a

dry, well-ventilated space, away from direct sunlight, at a temperature between 0° and 30°C.



Date issued: 12/02/2021

Продукт: [Грунд Rust-Oleum защита от графити 10 л, Graffitishield Hydro](#)

Категория: [Битова химия](#)

Марка: [Марка Rust-Oleum](#)

Тип: [Грунд Rust-Oleum](#)