

Технически характеристики

Спрей Rust-Oleum технически за замразяване 0.5 л, X1 eXcellent Freeze&Release

X1 SHOCK SPRAY

DESCRIPTION

High quality rust releaser to loosen rusted parts by shocking, with a rapid temperature decrease and then using an advanced chemical action to penetrate, lubricate and release the components. Reinforced with BoroTecX™. This gives the advantages of outstanding lubrication properties and it repels water.

RECOMMENDED USE

Fasteners, connections fastened with screws. Releases rusted and seized screws, bolts, studs and other seized components.

SURFACE PREPARATION

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

APPLICATION CONDITIONS

Apply at temperatures between 5° and 35°C.

APPLICATION & THINNING: AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

SHELF LIFE

Talle B-Fari Byring.com 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.



Продукт: Спрей Rust-Oleum технически за замразяване 0.5 л, X1 eXcellent Freeze&Release

Категория: Спрейове Марка: Mapкa Rust-Oleum Тип: Спрей Rust-Oleum