

Технически характеристики

Спрей Rust-Oleum технически керамична грес 0.5 л, X1 eXcellent Ceramic Anti Seize

X1 CERAMIC ANTI SEIZE SPRAY

DESCRIPTION

Ceramic base grease, capable of withstanding extreme pressures and temperatures. The ceramic technology leaves an inert barrier of microscopic platelets which will help prevent seizure long after greases fail due to high temperature. It provides with an ultra thin film, giving lasting lubrication and protection.

RECOMMENDED USE

Lubricating bearings, gears, cables and chains etc. Protection of metal surfaces against rust. Lubricating locks, hinges, and other moving parts. Ideal for tracks and slide conveyors. Water resistant, can be used on water pumps etc.

SURFACE PREPARATION

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

APPLICATION CONDITIONS

Apply at temperatures between 5° and 35°C.

APPLICATION & THINNING: AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

SHELF LIFE

Talle B-Fari Byring. com 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.



Продукт: Спрей Rust-Oleum технически керамична грес 0.5 л, X1 eXcellent Ceramic Anti Seize

Категория: Спрейове Марка: Mapкa Rust-Oleum Тип: Спрей Rust-Oleum