



# BODY SPRAY 950

- VOC compliant with the regulations
- A combination of caoutchouc/synthetic resin which has excellent adhesion
- It can be painted over immediately "wet to wet" using synthetic paints or with one or two component acrylic paints, after drying
- Remains permanently elastic
- Fast drying

## General Technical Description

- 2-3 passes
- Dust free 10-12 mins at 18-22 °C

### Surface :

- Inside bottom parts of the car body
- Outside bottom parts of the car body

### Pretreatment / Cleaning of substrate:



Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL / BODY 771 ANTISIL FAST


- Make sure the surface is air dried rather than wiped dry



- Make sure you always use appropriate face protection

## Product Application:

⇒ Apply on the inside and outside bottom parts of the car body



Shake well before using



2-3 coats approximately 20-30 microns



Dust free 10-12 mins Full hardness within at 18-22 °C



<b>Flash Point:</b> -97 °C	
<b>Specific Gravity:</b> - g/ cm <sup>3</sup>	
<b>Solid Content (No thinner):</b> 22% Weight	
VOC (2001/42/EC) 2004/42/IIIB(e)(840)575	
This product is an aerosol product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 575g/L	
<b>Remarks:</b>	
<ul style="list-style-type: none"> <li>• Always try to use the product in accordance with the specifications provided.</li> <li>• It can be used by countries that do not adopt the VOC legislation as well.</li> <li>• Shake thoroughly before use.</li> <li>• Shake for 1-2 mins after agitator ball has started to rattle. After preparing the area to be painted ensure it to be free from dirt, wax, oil etc. Test on a similar surface using a back and forth action.</li> <li>• Spray at a distance of 25 cm thinly applied coats build up at 5-10 minutes intervals will achieve best results. Leave for 24 hours to harden.</li> <li>• Optimum operating range 10-25 °C</li> <li>• Store in a cool place and use within 12 months for best results.</li> </ul>	

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 1/2008, November 2008.

