

Multi-purpose grease construction/agriculture

EP-2 grease with a lithium/calcium base

- Resistant to high pressure due to EP additive
- High shearing strength
- High resistance to weathering
- High resistance to water and steam



| | |
|--|---|
| Soap base | Lithium/calcium |
| Lubricant code | KP2K-30 |
| Min./max. temperature conditions | -30 to 120 °C |
| Colour | Blue |
| NLGI grade/conditions | 2/with DIN 51818 |
| Base oil viscosity, kinematic/conditions | 300 mm ² /s/at 40 °C |
| Min./max. worked penetration/conditions | 265 x 0.1 mm-295 x 0.1 mm/in accordance with DIN ISO 2137 |
| Corrosion protection period/category | Corrosion category 0-0 |
| VKA welding load | 3400 N |
| Shelf life from production | 48 Month |
| Oil basis | Mineral oil |

| Weight of content | Container | Art. no. | P. Qty. |
|-------------------|------------------------|---------------------|---------|
| 400 g | Cartridge | 0893 874 1 | 1/12 |
| 400 g | Cartridge Lube Shuttle | 0893 874 400 | 1/12 |
| 500 g | Screwed cartridge | 0893 874 102 | 1/12 |

Details/Application

Particularly suitable for heavily loaded devices and machines, such as construction and agricultural machinery. The operational area covers a wide range of applications such as heavily loaded roller bearings and ball bearings, work roll bearings and support roller bearings, hot and cold shear systems, roller bearings and plain bearings, etc. Ideal for use even in extremely unfavourable conditions, such as with wetness, vapour, dust, mud and under extreme weather conditions.



Notice

Greases are supplied in plastic cartridges. The plastic cartridges improve storage (they prevent the grease from oozing out at high temperature). Store cartridges upright in a cool, dry place! The operating instructions of the vehicle, machinery and