



MAGPRO 40/2S

**PRIME
LINE**



Generous stroke of 165 mm (enables, among other things, the use of longer drills)

- 2 speeds: 1 for core drilling and 1 for twist drilling
- 17.000 N magnetic adhesion
- Overload protection
- Integrated cooling system

Scope of delivery:

Lashing strap, coolant tank, tool, chip protection, carry case



Optional: 13 mm drill chuck & adapter for direct use in the quick-release chuck
Art. 490152A



Generous stroke is easily adjustable

| Technical specifications | |
|-------------------------------|--|
| Power input | 1.100 W |
| Voltage | 230 V / 50 Hz 115 V / 60 Hz |
| No load/full load speeds | core drilling 650 / 465 min ⁻¹ twist drilling 1100 / 790 min ⁻¹ |
| Shank | 19 mm Weldon |
| Core drill max. Ø x L | 12 - 40 x 110 mm |
| Max. Ø countersink | 30 mm |
| Max. twist drilling depth x Ø | 13 x 100 mm |
| Stroke | 85 mm for normal core drills, up to 165 mm for twist drill |
| Magnetic adhesion | 17.000N |
| Magnetic surface | 170 x 85 mm |
| Cooling system | integrated, automatic |
| Net weight | 13 kg |

| Description | Reference |
|--|-----------|
| Magpro 40 / 2s delivery in a carry case with lashing strap, service equipment and coolant tank, 230V | 490142 |
| As above, 115V | 490142NA |
| Accessories (optional) | Reference |
| HSS-Co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin | 490145 |
| Carbide tipped core drill set 30 mm Ø 1x12, 1x 14, 1x16, 1x18, 1x20, 1x22 mm + pilot pin | 490148 |
| Gold finger core drill set TiN-coated 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin | 490145TiN |
| HSS-Co core drill set Ø 9/16", 5/8", 11/16", 3/4", 13/16", 15/16" x 1 + pilot pin | 490145iN |
| Drill chuck and adapter 13 mm | 490152A |
| Weldon adapter 19 mm for Fein core drills with quick-in shank and + pilot pin / centering pin | 490154 |
| Magnetic chip collector | 490153 |
| High-performance drilling and cutting oil spray for optimal cooling and higher cutting performance (Content: 400 ml) | 490020 |
| HSS-countersinks with Weldon 19 shank on page 69 | |