

# MAGPRO 100 M30

Core drilling up to Ø 100 mm  
Thread cutting up to M30  
Twist drilling up to Ø 32 mm


- Heavy duty reversible motor unit
- 4 Gears, 8 Speeds
- Highest stability without extra support
- Overload protection

### Scope of delivery:

Steel case, MT3/Weldon 19 & 32 adapter, safety chain, carabina and hexagon key.



Delivered in carry case



Patented guide

### Technical specifications

Power input	1.880 W
Voltage	230 V / 50 Hz
No load speeds	100/70 min <sup>-1</sup> 195/130 min <sup>-1</sup> 330/225 min <sup>-1</sup> 600/405 min <sup>-1</sup>
Shank	19/32 mm Weldon, MT3
Max. tapping capacity	M4-M30
Max. Ø core drills	100 mm
Max. Ø twist drills (MT3)	32 mm
Magnetic adhesion	17.600 N
Dimensions [mm]	530 (790) x 205 x 300
Stroke	260 mm
Net weight	26 kg

**PRIME  
LINE**



Thread cutting, twist- & core drilling  
(accessories might be necessary)

Description	Reference
Magpro 100 M30 - in steel case with MT3 Weldon 19 & 32 adapter, safety chain, carabina and hexagon key	491100N
Accessories (optional)	Reference
HSS-Co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145
Carbide tipped core drill set 30 mm Ø 1x12, 1x14, 1x16, 1x18, 1x20, 1x22 mm + pilot pin	490148
Gold finger core drill set TiN-coated 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145TiN
HSS-Co core drill set Ø 9/16", 5/8", 11/16", 3/4", 13/16", 15/16" x 1 + pilot pin	490145IN
MT3 quick change adapter set for thread cutter M3-M14	490162
Quick change insert M3-M14 (single)	490162 M3-14
MT3 quick change adapter set for thread cutter M5-M22	490165
Quick change insert M5-M22 (single)	490165 M5-22
MT3 quick change adapter set for thread cutter M14-M30	490169
Quick change insert M14-M30 (single)	490169 M14-30
MT3 / 19 mm adapter	490167
Weldon 19/MT3 adapter for magnetic drills from Ø 61 mm	490163
Drill chuck and adapter 16 mm	490164
High-performance drilling and cutting oil spray (400 ml)	490020
Magnetic chip collector	490153
HSS-countersinks with Weldon 19 shank on page 69	