

OPTIdrill® DM 35PF with automatic spindle sleeve feed

- ▶ Weldon shank



- > automatic
- > Return



Fig. : with optional accessories



Core drilling

Drilling bit Ø max.	Ø 38 mm
Drilling bit depth max.	35 mm

OPTIdrill® DM 35V

- ▶ Continuously variable speed control
- ▶ Quick clamping chuck
- ▶ Weldon shank



Fig. : with optional accessories



Core drilling

Drilling bit Ø max.	Ø 35 mm
Drilling bit depth max.	35 mm

Twist drill

Drilling bit Ø max.	Ø 13 mm
---------------------	---------

Model	DM 35PF	DM 35V
Article no.	3071435	3071135
Technical specifications		
Electrical connection	230 V / 1 Ph ~50 Hz	230 V / 1 Ph ~50 Hz
Motor output	1.6 kW	1.55 kW
Carriers		
Drill bit adapter	Weldon 3/4"	Weldon 3/4"
Tool shank	Weldon shank Ø 19 mm (3/4")	Weldon shank Ø 19 mm (3/4")
Magnetic foot		
Magnetic foot dimensions	166 x 80 mm	166 x 80 mm
Magnetic attraction force	16 KN	14.8 KN
Speeds		
Speed without load	810 rpm	120 - 830 rpm stepless
Dimensions		
Length x width x height	350 x 250 x 430 mm	250 x 220 x 300 - 470 mm
Weight	14 kg	10.8 kg