


OPTIdrill® DM 50V

- ▶ Continuously variable speed control
- ▶ Quick clamping chuck
- ▶ Weldon shank



> for perfect alignment



Fig.: with optional accessories



Core drilling	
Drilling bit Ø max.	Ø 50 mm
Drilling bit depth max.	50 mm
Twist drill	
Drilling bit Ø max.	Ø 13 mm

OPTIdrill® DM 60V

- ▶ Continuously variable speed control
- ▶ Quick clamping chuck
- ▶ MT collet



Fig.: with optional accessories



Core drilling	
Drilling bit Ø max.	Ø 60 mm
Drilling bit depth max.	50 mm
Twist drill	
Drilling bit Ø max.	Ø 23 mm

Model	DM 50V	DM 60V
Article no.	3071150	3071160
Technical specifications		
Electrical connection	230 V / 1 Ph ~50 Hz	230 V / 1 Ph ~50 Hz
Motor output	1.7 kW	1.89 kW
Carriers		
Drill bit adapter	Weldon 3/4"	MT 2 and Weldon 3/4"
Tool shank	Weldon shank Ø 19 mm (3/4")	Weldon shank Ø 19 mm (3/4")
Magnetic foot		
Magnetic foot dimensions	166 x 80 mm	202 x 103 mm
Magnetic attraction force	15,6 KN	16 KN
Speeds		
Speed without load	100 - 810 rpm stepless	240 - 440 rpm stepless
Dimensions		
Length x width x height	250 x 220 x 300 - 470 mm	330 x 240 x 450 - 650 mm
Weight	11 kg	18.3 kg