

Дюза Wagner за лако-бояджийска техника комплект с бял филтър и уплътнение 0.64 мм, 40 °, Trade Tip 3 425



| Application | Nozzle marking | Bore (in inch / mm) | Spray angle (in °) | Jet width (in mm ¹) | Gun filter ² | Art.-No. |
|--|--------------------------------|------------------------|-----------------------|------------------------------------|-------------------------|----------|
| Water-thinnable and solvent-based enamels and paints, oils, mould release agents | 107 | 0.007 / 0.18 | 10 | 100 | red | 553107 |
| | 207 | 0.007 / 0.18 | 20 | 120 | red | 553207 |
| | 307 | 0.007 / 0.18 | 30 | 150 | red | 553307 |
| | 407 | 0.007 / 0.18 | 40 | 190 | red | 553407 |
| | 109 | 0.009 / 0.23 | 10 | 100 | red | 553109 |
| | 209 | 0.009 / 0.23 | 20 | 120 | red | 553209 |
| | 309 | 0.009 / 0.23 | 30 | 150 | red | 553309 |
| | 409 | 0.009 / 0.23 | 40 | 190 | red | 553409 |
| | 509 | 0.009 / 0.23 | 50 | 225 | red | 553509 |
| | 609 | 0.009 / 0.23 | 60 | 270 | red | 553609 |
| Synthetic resin varnishes, PVC enamels | 111 | 0.011 / 0.28 | 10 | 100 | red | 553111 |
| | 211 | 0.011 / 0.28 | 20 | 120 | red | 553211 |
| | 311 | 0.011 / 0.28 | 30 | 150 | red | 553311 |
| | 411 | 0.011 / 0.28 | 40 | 190 | red | 553411 |
| | 511 | 0.011 / 0.28 | 50 | 225 | red | 553511 |
| | 611 | 0.011 / 0.28 | 60 | 270 | red | 553611 |
| Enamels, undercoats, base coats, fillers | 113 | 0.013 / 0.33 | 10 | 100 | red | 553113 |
| | 213 | 0.013 / 0.33 | 20 | 120 | red | 553213 |
| | 313 | 0.013 / 0.33 | 30 | 150 | red | 553313 |
| | 413 | 0.013 / 0.33 | 40 | 190 | red | 553413 |
| | 513 | 0.013 / 0.33 | 50 | 225 | red | 553513 |
| | 613 | 0.013 / 0.33 | 60 | 270 | red | 553613 |
| | 813 | 0.013 / 0.33 | 80 | 330 | red | 553813 |
| | Fillers, anti-corrosive paints | 115 | 0.015 / 0.38 | 10 | 100 | yellow |
| 215 | | 0.015 / 0.38 | 20 | 120 | yellow | 553215 |
| 315 | | 0.015 / 0.38 | 30 | 150 | yellow | 553315 |
| 415 | | 0.015 / 0.38 | 40 | 190 | yellow | 553415 |
| 515 | | 0.015 / 0.38 | 50 | 225 | yellow | 553515 |
| 615 | | 0.015 / 0.38 | 60 | 270 | yellow | 553615 |
| 715 | | 0.015 / 0.38 | 70 | 300 | yellow | 553715 |
| 815 | | 0.015 / 0.38 | 80 | 330 | yellow | 553815 |
| Anti-corrosive paints, latex paints, emulsions | | 117 | 0.017 / 0.43 | 10 | 100 | yellow |
| | 217 | 0.017 / 0.43 | 20 | 120 | yellow | 553217 |
| | 317 | 0.017 / 0.43 | 30 | 150 | yellow | 553317 |
| | 417 | 0.017 / 0.43 | 40 | 190 | yellow | 553417 |
| | 517 | 0.017 / 0.43 | 50 | 225 | yellow | 553517 |
| | 617 | 0.017 / 0.43 | 60 | 270 | yellow | 553617 |
| | 717 | 0.017 / 0.43 | 70 | 300 | yellow | 553717 |
| | 817 | 0.017 / 0.43 | 80 | 330 | yellow | 553817 |
| | 219 | 0.019 / 0.48 | 20 | 120 | white | 553219 |
| | 319 | 0.019 / 0.48 | 30 | 150 | white | 553319 |
| | 419 | 0.019 / 0.48 | 40 | 190 | white | 553419 |
| | 519 | 0.019 / 0.48 | 50 | 225 | white | 553519 |
| | 619 | 0.019 / 0.48 | 60 | 270 | white | 553619 |
| 719 | 0.019 / 0.48 | 70 | 300 | white | 553719 | |
| 819 | 0.019 / 0.48 | 80 | 330 | white | 553819 | |
| 919 | 0.019 / 0.48 | 90 | 385 | white | 553919 | |

¹Spray width (mm) at an approx. distance of 30 cm to the object and 10 MPa pressure, with synthetic resin varnish 20 DIN seconds.

²Red: 180 mesh, extra fine, yellow: 100 mesh, fine, white: 50 mesh, medium, green: 30 mesh, coarse



| Application | Nozzle marking | Bore (in inch / mm) | Spray angle (in °) | Jet width (in mm ¹) | Gun filter ² | Art.-No. |
|--|---------------------|------------------------|-----------------------|------------------------------------|-------------------------|----------|
| Flame retardants | 221 | 0.021 / 0.53 | 20 | 120 | white | 553221 |
| | 321 | 0.021 / 0.53 | 30 | 150 | white | 553321 |
| | 421 | 0.021 / 0.53 | 40 | 190 | white | 553421 |
| | 521 | 0.021 / 0.53 | 50 | 225 | white | 553521 |
| | 621 | 0.021 / 0.53 | 60 | 270 | white | 553621 |
| | 721 | 0.021 / 0.53 | 70 | 300 | white | 553721 |
| | 821 | 0.021 / 0.53 | 80 | 330 | white | 553821 |
| | Roof linings | 223 | 0.023 / 0.58 | 20 | 120 | white |
| 323 | | 0.023 / 0.58 | 30 | 150 | white | 553323 |
| 423 | | 0.023 / 0.58 | 40 | 190 | white | 553423 |
| 523 | | 0.023 / 0.58 | 50 | 225 | white | 553523 |
| 623 | | 0.023 / 0.58 | 60 | 270 | white | 553623 |
| 723 | | 0.023 / 0.58 | 70 | 300 | white | 553723 |
| 823 | | 0.023 / 0.58 | 80 | 330 | white | 553823 |
| Thick layered materials, corrosion protection, spraying fillers | | 225 | 0.025 / 0.64 | 20 | 120 | white |
| | 325 | 0.025 / 0.64 | 30 | 150 | white | 553325 |
| | 425 | 0.025 / 0.64 | 40 | 190 | white | 553425 |
| | 525 | 0.025 / 0.64 | 50 | 225 | white | 553525 |
| | 625 | 0.025 / 0.64 | 60 | 270 | white | 553625 |
| | 725 | 0.025 / 0.64 | 70 | 300 | white | 553725 |
| | 825 | 0.025 / 0.64 | 80 | 330 | white | 553825 |
| | 227 | 0.027 / 0.69 | 20 | 120 | white | 553227 |
| | 327 | 0.027 / 0.69 | 30 | 150 | white | 553327 |
| | 427 | 0.027 / 0.69 | 40 | 190 | white | 553427 |
| | 527 | 0.027 / 0.69 | 50 | 225 | white | 553527 |
| | 627 | 0.027 / 0.69 | 60 | 270 | white | 553627 |
| | 827 | 0.027 / 0.69 | 80 | 330 | white | 553827 |
| | 229 | 0.029 / 0.75 | 20 | 120 | white | 553229 |
| | 329 | 0.029 / 0.75 | 30 | 150 | white | 553329 |
| | 429 | 0.029 / 0.75 | 40 | 190 | white | 553429 |
| | 529 | 0.029 / 0.75 | 50 | 225 | white | 553529 |
| | 629 | 0.029 / 0.75 | 60 | 270 | white | 553629 |
| | 231 | 0.031 / 0.79 | 20 | 120 | white | 553231 |
| | 331 | 0.031 / 0.79 | 30 | 150 | white | 553331 |
| | 431 | 0.031 / 0.79 | 40 | 190 | white | 553431 |
| | 531 | 0.031 / 0.79 | 50 | 225 | white | 553531 |
| | 631 | 0.031 / 0.79 | 60 | 270 | white | 553631 |
| | 731 | 0.031 / 0.79 | 70 | 300 | white | 553731 |
| | 831 | 0.031 / 0.79 | 80 | 330 | white | 553831 |
| | 233 | 0.033 / 0.84 | 20 | 120 | white | 553233 |
| | 333 | 0.033 / 0.84 | 30 | 150 | white | 553333 |
| | 433 | 0.033 / 0.84 | 40 | 190 | white | 553433 |
| | 533 | 0.033 / 0.84 | 50 | 225 | white | 553533 |
| | 633 | 0.033 / 0.84 | 60 | 270 | white | 553633 |
| 235 | 0.035 / 0.9 | 20 | 120 | white | 553235 | |
| 335 | 0.035 / 0.9 | 30 | 150 | white | 553335 | |
| 435 | 0.035 / 0.9 | 40 | 190 | white | 553435 | |
| 535 | 0.035 / 0.9 | 50 | 225 | white | 553535 | |
| 635 | 0.035 / 0.9 | 60 | 270 | white | 553635 | |
| 735 | 0.035 / 0.9 | 70 | 300 | white | 553735 | |
| 439 | 0.039 / 0.99 | 40 | 190 | white | 553439 | |
| 539 | 0.039 / 0.99 | 50 | 225 | white | 553539 | |
| 639 | 0.039 / 0.99 | 60 | 270 | white | 553639 | |

¹Spray width (mm) at an approx. distance of 30 cm to the object and 10 MPa pressure, with synthetic resin varnish 20 DIN seconds.

²Red: 180 mesh, extra fine, yellow: 100 mesh, fine, white: 50 mesh, medium, green: 30 mesh, coarse



| Application | Nozzle marking | Bore (in inch / mm) | Spray angle (in °) | Jet width (in mm ¹) | Gun filter ² | Art.-No. |
|-------------------------|----------------|------------------------|-----------------------|------------------------------------|-------------------------|----------|
| Heavy-duty applications | 243 | 0.043 / 1.1 | 20 | 120 | green | 553243 |
| | 443 | 0.043 / 1.1 | 40 | 190 | green | 553443 |
| | 543 | 0.043 / 1.1 | 50 | 225 | green | 553543 |
| | 643 | 0.043 / 1.1 | 60 | 270 | green | 553643 |
| | 445 | 0.045 / 1.14 | 40 | 190 | green | 553445 |
| | 545 | 0.045 / 1.14 | 50 | 225 | green | 553545 |
| | 645 | 0.045 / 1.14 | 60 | 270 | green | 553645 |
| | 451 | 0.051 / 1.3 | 40 | 190 | green | 553451 |
| | 551 | 0.051 / 1.3 | 50 | 225 | green | 553551 |
| | 651 | 0.051 / 1.3 | 60 | 270 | green | 553651 |
| | 252 | 0.052 / 1.32 | 20 | 120 | green | 553252 |
| | 455 | 0.055 / 1.4 | 40 | 190 | green | 553455 |
| | 555 | 0.055 / 1.4 | 50 | 225 | green | 553555 |
| | 655 | 0.055 / 1.4 | 60 | 270 | green | 553655 |
| | 261 | 0.061 / 1.55 | 20 | 120 | green | 553261 |
| | 461 | 0.061 / 1.55 | 40 | 190 | green | 553461 |
| | 561 | 0.061 / 1.55 | 50 | 225 | green | 553561 |
| | 661 | 0.061 / 1.55 | 60 | 270 | green | 553661 |
| | 263 | 0.063 / 1.6 | 20 | 120 | green | 553263 |
| | 463 | 0.063 / 1.6 | 40 | 190 | green | 553463 |
| | 565 | 0.065 / 1.65 | 50 | 225 | green | 553565 |
| | 665 | 0.065 / 1.65 | 60 | 270 | green | 553665 |
| | 267 | 0.067 / 1.7 | 20 | 120 | green | 553267 |
| 467 | 0.067 / 1.7 | 40 | 190 | green | 553467 | |

¹Spray width (mm) at an approx. distance of 30 cm to the object and 10 MPa pressure, with synthetic resin varnish 20 DIN seconds.

²Red: 180 mesh, extra fine, yellow: 100 mesh, fine, white: 50 mesh, medium, green: 30 mesh, coarse

Продукт: [Дюза Wagner за лако-бояджийска техника комплект с бял филтър и уплътнение 0.64 мм, 40 °, Trade Tip 3 425](#)

Категория: [Помпи за боядисване](#)

Марка: [Wagner](#)

Тип: [Дюза Wagner](#)