

A51CRM

BATH POP-UP WASTE, OVERFLOW AND TRAP, CHROME

Application:

- To drain the water from the bath to the waste
- For standard sizes bathtubs
- For bathtubs with drain outlet Ø52 mm

Features:

- Bath waste and overflow system
- Wet odour trap with swivel elbow
- Closing waste by pop-up
- Overflow flexi pipe

Standards:

ČSN EN 274

Technical parameters:

Trap	50 mm
Flow rate	51.6 l/min.
Overflow flow rate	42 l/min.
Resistance of odour traps against pressure	588 Pa
Thermal resistance	95 °C

Scope of supply:

- Trap body with overflow
- Chrome-plated plastic control knob
- Chrome-plated plastic plug
- Chrome-plated stainless steel grid
- The odour trap of polypropylene, thermally and chemically resistant, longitudinally welded
- Assembly kit
- Profiled seal

Logistic information:

Dimensions (piece)	380×145×85 mm
Quantity (packing)	20 pcs
Quantity (pallet)	320 pcs

Order number:

Code	EAN	Length (L)	Weight (piece)
A51CRM	8594045934229	57 mm	0.6538 kg
A51CRM-80	8594045936605	80 mm	0.7488 kg
A51CRM-100	8594045937992	100 mm	0.7729 kg
A51CRM-120	8594045937824	120 mm	0.7924 kg

