A508KM

BATH CLICK/CLACK WASTE, OVERFLOW FILLER, METAL -**CHROME**

Application:

- For filling the bath by overflow
 To drain the water from the bath to the waste
- For standard sizes bathtubs
- For bathtubs with drain outlet Ø52 mm

- Bath overflow filler, waste and trap system
- Aerator Neoperl easy access and exchange
- Control shaft made out of stainless steel
- Water does not flow down on the side of the bathtub and does not leave marks
- Space-saving design in the bathtub visible only control knob
- Easy installation with three stainless steel screws
- Wet odour trap with swivel elbow
- Closing waste using the CLICK/CLACK
- Overflow flexi pipe
- Side G1/2" fitting for filling of pre-mixed water

Standards:

ČSN EN 274

Technical parameters:

Trap	50 mm
Flow rate	48.6 l/min.
Overflow flow rate	42 l/min.
Resistance of odour traps against pressure	588 Pa
Thermal resistance	95 °C

Scope of supply:

- Trap body with overflow
 Chrome-plated plastic control knob
- Chrome-plated metal plug
- Chrome-plated brass outlet
- The odour trap of polypropylene, thermally and chemically resistant, longitudinally welded
- Assembly kit
- Profiled seal

Logistic information:

380×210×95 mm
12 pcs
192 pcs

Order number:

Code	EAN	Length (L)	Weight (piece)
A508KM	8595580522469	57 mm	0.9669 kg
A508KM-80	8595580523954	80 mm	0.978 kg
A508KM-100	8595580523930	100 mm	0.994 kg
A508KM-120	8595580523947	120 mm	1.0148 kg



