



PN10 / PN16

BORU/PIPE DN	FLANŞ/FLANGE					BOYUN/NECK d ₃	ALIN ÇIKTIŞI / RAISED FACE		DELİKLER / DRILLINGS			AĞIRLIK (WEIGHT) kg
	R	D	b EN 1092-1	k	h		d ₄ EN 1092-1	f EN 1092-1	n	saplama (screw)	d ₂	
10	R 3/8"	90	16	60	22	30	40	2	4	M12	14	0,544
15	R 1/2"	95	16	65	22	35	45	2	4	M12	14	0,613
20	R 3/4"	105	18	75	26	45	58	2	4	M12	14	0,91
25	R 1"	115	18	85	28	52	68	2	4	M12	14	1,1
32	R 1 1/4"	140	18	100	30	60	78	2	4	M16	18	1,6
40	R 1 1/2"	150	18	110	32	70	88	2	4	M16	18	1,78
50	R 2"	165	18	125	32	84	102	2	4	M16	18	2,43
65	R 2 1/2"	185	18	145	32	104	122	2	8	M16	18	3,18
80	R 3"	200	20	160	34	118/120	138	2	8	M16	18	4,12
100	R 4"	220	20	180	40	140	158	2	8	M16	18	4,47
125	R 5"	250	22	210	44	168/170	188	2	8	M16	18	6,13
150	R 6"	285	22	240	44	195/190	212	2	8	M20	22	7,29

* Ölçüler mm.'dir / Dimensions are in mm.

PN25 / PN40

BORU/PIPE DN	FLANŞ/FLANGE					BOYUN/NECK d ₃	ALIN ÇIKTIŞI / RAISED FACE		DELİKLER / DRILLINGS			AĞIRLIK (WEIGHT) kg
	R	D	b EN 1092-1	k	h		d ₄ EN 1092-1	f EN 1092-1	n	saplama (screw)	d ₂	
10	R 3/8"	90	16	60	22	30	40	2	4	M12	14	0,63
15	R 1/2"	95	16	65	22	35	45	2	4	M12	14	0,71
20	R 3/4"	105	18	75	26	45	58	2	4	M12	14	1,03
25	R 1"	115	18	85	28	52	68	2	4	M12	14	1,28
32	R 1 1/4"	140	18	100	30	60	78	2	4	M16	18	1,87
40	R 1 1/2"	150	18	110	32	70	88	2	4	M16	18	2,14
50	R 2"	165	20	125	34	84	102	2	4	M16	18	2,85
65	R 2 1/2"	185	22	145	38	104	122	2	8	M16	18	3,85
80	R 3"	200	24	160	40	118	138	2	8	M16	18	4,8
100	R 4"	235	24	190	44	145	162	2	8	M20	22	6,43
125	R 5"	270	26	220	48	170	188	2	8	M24	26	8,77
150	R 6"	300	28	250	52	200	218	2	8	M24	26	10,5

* Ölçüler mm.'dir / Dimensions are in mm.