

## STAINLESS STEEL CAM-LOCK COUPLERS ( 2241-2248 )

Stainless steel cam-lock couplings for all common fluids of 2<sup>nd</sup> group.  
According to MIL-C-27487 and A-A 59326 standards.  
NBR gasket with the couplers.



**Size :** DN15 to DN100 (1/2" to 4")  
**Connection :** Female, Male BSP and hose coupling  
**Min Temperature :** -10°C  
**Max Temperature :** +80°C  
**Max Pressure :** 16 Bars  
**Specifications :** Stainless steel fittings  
NBR gasket  
Stainless steel cam  
According to MIL-C-27487 and A-A 59326

**Materials :** Stainless steel ASTM A351 CF8M

## STAINLESS STEEL CAM-LOCK COUPLERS ( 2241-2248 )

### SPECIFICATIONS :

- Stainless steel fittings
- NBR gasket ( only for couplers )
- According to MIL-C-27487 and A-A 59326

### USE :

- For all common fluids of 2<sup>nd</sup> group
- Min and max Temperature Ts : - 10°C to + 80°C
- Max Pressure Ps : See the table thereafter

| DN         | 1/2" | 3/4" | 1" | 1"1/4 | 1"1/2 | 2" | 2"1/2 | 3" | 4" |
|------------|------|------|----|-------|-------|----|-------|----|----|
| Ps ( Bar ) | 11   | 18   | 18 | 18    | 18    | 18 | 16    | 14 | 14 |

### RANGE :


- Female adapter type A **Ref.2241** DN 1/2" to DN 4"
- Male coupler type B **Ref.2242** DN 1/2" to DN 4"
- Hose coupler type C **Ref.2243** DN 1/2" to DN 4"
- Female coupler type D **Ref.2244** DN 1/2" to DN 4"
- Hose adapter type E **Ref.2245** DN 1/2" to DN 4"
- Male adapter type F **Ref.2246** DN 1/2" to DN 4"
- Cap coupler type DC **Ref.2247** DN 1/2" to DN 4"
- Plug adapter type DP **Ref.2248** DN 1/2" to DN 4"
- **Other gasket on demand : EPDM , FKM and FKM+PTFE**

### TEMPERATURE AND REFERENCE FOR GASKET NBR, EPDM, FKM AND FKM+PTFE :

| GASKET | TEMPERATURE          | 1/2"    | 3/4"    | 1"      | 1"1/4   | 1"1/2   | 2"      | 2"1/2   | 3"      | 4"      |
|--------|----------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| NBR    | From -10°C to +80°C  | 9830860 | 9830861 | 9830862 | 9830863 | 9830864 | 9830865 | 9830866 | 9830867 | 9830868 |
| EPDM   | From -10°C to +130°C | 9830850 | 9830851 | 9830852 | 9830853 | 9830854 | 9830855 | 9830856 | 9830857 | 9830858 |
| FKM    | From -10°C to +180°C | 9830870 | 9830871 | 9830872 | 9830873 | 9830874 | 9830875 | 9830876 | 9830877 | 9830878 |

## STAINLESS STEEL CAM-LOCK COUPLERS ( 2241-2248 )

### MATERIALS :



| Item | Designation | Materials      |
|------|-------------|----------------|
| 1    | Body        | ASTM A351 CF8M |
| 2    | Gasket      | NBR            |
| 3    | Cam         | ASTM A351 CF8M |
| 4    | Ring        |                |

### REPAIRABILITY :




| *Gasket (Item 2) |          |           |          |
|------------------|----------|-----------|----------|
| DN               | Ref. NBR | Ref. EPDM | Ref. FKM |
| DN1/2"           | 9830860  | 9830850   | 9830870  |
| DN3/4"           | 9830861  | 9830851   | 9830871  |
| DN1"             | 9830862  | 9830852   | 9830872  |
| DN1"1/4          | 9830863  | 9830853   | 9830873  |
| DN1"1/2          | 9830864  | 9830854   | 9830874  |
| DN2"             | 9830865  | 9830855   | 9830875  |
| DN2"1/2          | 9830866  | 9830856   | 9830876  |
| DN3"             | 9830867  | 9830857   | 9830877  |
| DN4"             | 9830868  | 9830858   | 9830878  |

## STAINLESS STEEL CAM-LOCK COUPLERS ( 2241-2248 )


### SIZE ( in mm ) :

- Cap coupler type DC Ref.2247



| REF. | DN         | 1/2"  | 3/4"  | 1"    | 1"1/4 | 1"1/2 | 2"   | 2"1/2 | 3"    | 4"    |
|------|------------|-------|-------|-------|-------|-------|------|-------|-------|-------|
| 2247 | Ø A        | 24.3  | 32.5  | 37.3  | 46    | 54    | 63.8 | 76.5  | 92.2  | 120.2 |
|      | L1         | 34    | 36.5  | 41.7  | 47.6  | 51    | 54   | 58    | 62.5  | 65    |
|      | L2         | 29    | 31.5  | 36    | 41    | 42.5  | 48   | 51.5  | 53    | 55    |
|      | Weig. (Kg) | 0.156 | 0.183 | 0.260 | 0.415 | 0.456 | 0.69 | 0.847 | 1.195 | 1.924 |

- Cap adapter type DP Ref.2248



| REF. | DN         | 1/2"  | 3/4"  | 1"    | 1"1/4 | 1"1/2 | 2"    | 2"1/2 | 3"    | 4"    |
|------|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 2248 | Ø A        | 24    | 32.4  | 36.7  | 45.5  | 53.5  | 63    | 75.8  | 91.5  | 119.5 |
|      | Ø B        | 14.17 | 21.9  | 24.6  | 30.2  | 38    | 46.85 | 58.4  | 75    | 102.4 |
|      | L1         | 31    | 30    | 37.4  | 43    | 44.2  | 48    | 53.5  | 56.5  | 58    |
|      | Weig. (Kg) | 0.089 | 0.084 | 0.142 | 0.236 | 0.299 | 0.443 | 0.679 | 0.959 | 1.514 |

### STANDARDS :

- Manufacturer certified ISO 9001 : 2015
- Directive 2014/68/EU : Products excluded from directive (Article 4, § 3)
- Designing according to MIL-C-27487 and A-A 59326
- Threaded female BSP cylindrical according to ISO 228-1 and male BSP conical according to ISO 7-1 R

**ADVICE :** Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.  
The customer must check the right choice of the products with the real service conditions.