


ISO 7046 EN -

DIN 965

d	M3	M4	M5	M6	M8
P	0,5	0,7	0,8	1	1,25
dk	5,6	7,5	9,2	11	14,5
k (max)	1,65	2,2	2,5	3	4
Nr. Phillips (H)	1	2	2	3	4

L\d: Peso/Weight 1000 ud. kg

4	0,291				
5	0,335	0,676			
6	0,379	0,754	1,210		
8	0,467	0,900	1,450	2,190	
10	0,555	1,060	1,700	2,540	5,030
12	0,643	1,220	1,950	2,890	5,670
14	0,731	1,370	2,190	3,250	6,300
16	0,820	1,530	2,440	3,610	6,940
18	0,908	1,680	2,690	3,950	7,570
20	0,996	1,840	2,940	4,310	8,210
22	1,080	1,990	3,180	4,660	8,840
25	1,220	2,220	3,550	5,190	9,790
28	1,350	2,460	3,930	5,720	10,70
30	1,440	2,610	4,160	6,080	11,70
35		2,990	4,760	6,960	13,00
40		3,360	5,390	7,840	14,60
45			6,020	8,730	16,20
50			6,650	9,610	17,80
55					19,40

CALIDADES/GRADES:

4.6	4.8	5.6	5.8	6.8	8.8	10.9	12.9	A2	A4
-----	-----	-----	-----	-----	-----	------	------	----	----

BBW