

EJOT® window screw type Super-E



Cross references

Bit cross recess

Application range

- > Fastening of tilt and turn fittings in PVC profiles and in steel or GRP inserts
- > Fixing locking plates, strips and bearings



Properties

- > Cost-effective screw for fittings with one-start thread
- > Under-head serrations for increased safety against stripping
- > Slightly curved head for flawless appearance even with bevelled installation
- > Roll-sorted quality for automated fastening
- > Case-hardened steel
- > EJOSEAL is an inorganic, transparent sealant, to significantly increase the corrosion and heat resistance of fastening elements with zinc or zinc alloy coatings. EJOSEAL does not contain wax and is ideally suitable for direct fastening into plastic.

Processing information

- > Can also be fastened in steel, pre-drilling required (see chart)
- > Can also be fastened in GRP, pre-drilling might be required

Technical data



Online shop



Sheet thickness	Pre-drilling diameter
1.5 mm	3.0 mm
2.0 mm	3.0 mm
2.5 mm	3.0 mm

Order description	Diameter [mm]	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
EJOSEAL						
Window screw Super-E 4.2x16	4.2	16	1,000		2 253 416 607	4061245041438
Window screw Super-E 4.2x20	4.2	20	1,000		2 253 420 607	4061245041421
Window screw Super-E 4.2x22	4.2	22	1,000		2 253 422 607	4061245041414
Window screw Super-E 4.2x25	4.2	25	1,000		2 253 425 607	4061245041407
Window screw Super-E 4.2x28	4.2	28	1,000		2 253 428 607	4061245041391
Window screw Super-E 4.2x30	4.2	30	1,000		2 253 430 607	4061245041384
Window screw Super-E 4.2x35	4.2	35	1,000		2 253 435 607	4061245041377
Window screw Super-E 4.2x40	4.2	40	1,000		2 253 440 607	4061245041360
Window screw Super-E 4.2x45	4.2	45	1,000		2 253 445 607	4061245041353
Window screw Super-E 4.2x55	4.2	55	1,000		2 253 455 607	4061245041346

Order information: head finish in RAL colours upon request. TX15 drive upon request.