



DRILL MOTOR DM 370 220-240 V | 1ph | 50 Hz | EU

DM 370 is a powerful and sturdy electric core drill for medium to heavy core drilling where reliability and high productivity is needed. Recommended diameter 25-250 mm. With aluminium motor housing to withstand tough handling and a carrying handle for ergonomic usage and additional impact protection of the drill motor. Equipped with Embedded Connectivity, an enhanced version of Husqvarna Fleet Services[™] for data analytics and insights into the health of the machine. Suitable for water evacuation, ventilation, angle drilling, stitch drilling and when you need to cut close to corners.

Motor

	DRILL MOTOR DM 370 220-240 V 1-ph 50 Hz EU
Rated input power	3.2 kW
Frequency	50 Hz
Voltage	220-240 V

Phases	1 ph
Power source	Corded

Equipment

	DRILL MOTOR DM 370 220-240 V 1-ph 50 Hz EU
Drill bit diameter with stand, max	250 mm
Recommended drill bit diameter, min	25 mm
Coolant	Wet

Transmission

	DRILL MOTOR DM 370 220-240 V 1-ph 50 Hz EU
Number of gearbox speeds	3
Spindle speed unloaded gear 1	550 rpm
Spindle speed unloaded gear 2	1,070 rpm
Spindle speed unloaded gear 3	1,630 rpm

Product data

	DRILL MOTOR DM 370 220-240 V 1-ph 50 Hz EU
Water connector	G 1 / 4"
Water pressure, max	3 bar

Dimensions

	DRILL MOTOR DM 370 220-240 V 1-ph 50 Hz EU
Product size length	546 mm
Product size width	138 mm

Product size height	185 mm
Weight (complete product w/o side packed articles)	13.5 kg
Packaging length	625 mm
Packaging width	255 mm
Packaging height	300 mm
Article gross weight	16,600 g

Sound and noise

	DRILL MOTOR DM 370 220-240 V 1-ph 50 Hz EU
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	92 dB(A)

