

## Технически характеристики

# OPTi saw<sup>®</sup>s 275N / S 275NV

### Metal band saw with pivoting saw head.

S 275NV with continuously adjustable saw band speed

### Facts that impress in terms of quality, performance and price

- Low-noise running action
- Rugged cast design
- Excellent cutting precision thanks to vibration-free action
- Saw band lowering via hydraulic cylinder continuously adjustable by throttle valve
- Microswitch for automatic limit position cut-off
- Coolant system
- Equipped as a factory standard with bi-metal saw blade
- Adjustable material stop for batch work
- Rugged machine chassis
- Ball-bearing borne saw band guide

- ▶ Quick clamping vice, adjustable via hand wheel. Workpiece is clamped using a handy quick-clamping lever
- Easily legible scale for adjusting the angle
- Overload protection

#### S 275N

- Motor circuit switch
- ▶ Two switchable speeds

#### S 275NV

- Saw band speed continuously adjustable
- Speed change possible during operation

#### Pressure gauge

Weight

> Easy and accurate adjustment of the saw band tension



	-		
	> (	Coolant pump	
	Cı	utting areas	
0 °	Ø 225 mm	170 mm	150 x 245 mm
45°	Ø 145 mm	145 mm	145 x 180 mm
60°	Ø 90 mm	90 mm	90 x 120 mm

Dimensions

1235

The cutting area was determined for a full section. ns.

	The cu	itting	range	can	be	larger	in	case	ot	cut-of	fsec	tion
--	--------	--------	-------	-----	----	--------	----	------	----	--------	------	------

AQUACUT C1	3530030
> For cooling the cut	

	>	10	litres	
--	---	----	--------	--

Saw bands HSS bi-metal M 42					
Teeth per inch	Tooth angle	Art.no.			
5 - 8 tpi	0°	3357511			
5 - 8 tpi	3357512				
6 - 10 tpi	3357524				
6 - 10 tpi	3357510				
10 - 14 tpi	3357525				
Saw band set HSS bi-metal M 42   1 pc. Saw band 6 - 10 tpi; 6° 3357504   1 pc. Saw band 5 - 8 tpi; 0° 3357504   1 pc. Saw band 5 - 8 tpi; 6° 3357504					
"General saw band information" on page 220					

185 kg

S 275N Model S 275NV Article no. 3300260 3300265 **Technical specifications** 400 V / 3 Ph ~50 Hz 230 V / 1 Ph ~50 Hz Electrical connection Motor output 1.1 kW 1.5 kW Coolant pump motor 90 W **General instructions** Lifting the saw head manual Feed continuously variable Saw band speed 45 / 90 m/min 20 - 90 m/min Saw band dimensions 2 480 x 27 x 0.9 mm Cutting angle 0° to 60° Dimensions Length 1 400 mm Width without/with material stop 685 mm / 985 mm Height bottom/top limit position 1 235 mm / 1 700 mm

Fig.: S 275N

- from 20 to 90 m/min.

Ø 90 mm 90 mm