



Article code		1122304
Plug and drill Ø mm	$d_{nom}$	8
Length mm	$L$	140
Usable length mm	$t_{fix}$	70
Screw Ø mm	$d_s$	6
Screw length mm	$L_s$	145
Drilling hole Ø mm	$d_0$	8
Drilling depth mm	$h_0$	80
Setting depth min. mm	$h_{ef}$	70
Drive		PZ3
Clearance hole in fixture mm	$d_f$	8
<b>Packaging</b>		
Box contents		100
FS		FS61
Outer carton		600
SK		SK32
Quantity per pallet		14400
<b>Technical Data</b>		
Perforated Brick app. load (kN)		0.4
Lightweight Concrete app. load (kN)		0.15
Aerated Concrete app. load (kN)		
Bending moment (Nm) galv. steel $F_z = 0$ kN		3.4
Bending moment (Nm) galv. steel $F_z = 0.6$ kN		3.1
Bending moment (Nm) stainl. steel $F_z = 0$ kN		3.2
Bending moment (Nm) stainl. steel $F_z = 0.6$ kN		2.9
<b>Additional information</b>		
Weight FS		2.822 kg
Weight SK		16.932 kg
Type		8 x 140 / 70
<b>EAN-Code</b>		

EAN-Code FS		7610634111015
EAN-Code SK		7610634110902
Not part of the approval		
Important: without hammer drilling in perforated brick and lightweight concrete		
Values only valid when using Mungo safety screws		
Safety factor 5		
1 kN $\approx$ 100 kg		
Fz = existing central traction		
Approved loads: Tension, shear and combined loads according to approval Z-21.2-177		

Ташев-Галвинг ООД  
[www.tashev-galving.com](http://www.tashev-galving.com)