



|                                        |                  |                |
|----------------------------------------|------------------|----------------|
| Article code                           |                  | 1060120        |
| Plug and drill Ø mm                    | d <sub>nom</sub> | 10             |
| Max. drill cut Ø mm                    | d <sub>cut</sub> | 10.45          |
| Length mm                              | L                | 200            |
| Usable length mm                       | t <sub>fix</sub> | 130            |
| Setting depth min. mm                  | h <sub>ef</sub>  | 70             |
| Screw Ø mm                             | d <sub>s</sub>   | 7              |
| Screw length mm                        | L <sub>s</sub>   | 205            |
| Drilling hole Ø mm                     | d <sub>0</sub>   | 10             |
| Drilling depth mm                      | h <sub>0</sub>   | 80             |
| Drive                                  |                  | T40            |
| Clearance hole in fixture mm           | d <sub>f</sub>   | 10             |
| <b>Packaging</b>                       |                  |                |
| Box contents                           |                  | 50             |
| FS                                     |                  | FS51           |
| Outer carton                           |                  | 300            |
| SK                                     |                  | SK32           |
| Quantity per pallet                    |                  | 7200           |
| <b>Technical Data</b>                  |                  |                |
| Concrete C20/25 tension load (kN)      |                  | 2.0            |
| Perforated Brick tension load (kN)     |                  | 1.2            |
| Lightweight Concrete tension load (kN) |                  | 0.4            |
| Aerated Concrete tension load (kN)     |                  | 0.5            |
| Sandstone tension load (kN)            |                  | 0.6            |
| <b>Additional information</b>          |                  |                |
| Weight FS                              |                  | 3.287 kg       |
| Weight SK                              |                  | 19.450 kg      |
| Type                                   |                  | 10 x 200 / 130 |