

Article code		**1121924**
Plug and drill Ø mm	d_{nom}	**10**
Length mm	**L**	**240**
Usable length mm	t_{fix}	**170**
Screw Ø mm	d_s	**7**
Screw length mm	L_s	**245**
Drilling hole Ø mm	d_0	**10**
Drilling depth mm	h_0	**80**
Setting depth min. mm	h_{ef}	**70**
Spanner size	**SW**	**13**
Clearance hole in fixture mm	d_f	**10**
Packaging		
Box contents		**25**
Technical Data		
Perforated Brick app. load (kN)		**0.8**
Lightweight Concrete app. load (kN)		**0.25**
Aerated Concrete app. load (kN)		**0.3**
Bending moment (Nm) galv. steel Fz = 0 kN		**11.1**
Bending moment (Nm) galv. steel Fz = 0.6 kN		**10.6**
Bending moment (Nm) stainl. steel Fz = 0 kN		**10.4**
Bending moment (Nm) stainl. steel Fz = 0.6 kN		**9.9**
Edge distance (c) Sandstone with burden mm		**100**
Edge distance (c) Sandstone without burden mm		**250**
Edge distance (c) perforated brick with burden mm		**100**
Edge distance (c) perforated brick without burden mm		**250**
Edge distance (c) Hollow blocks made of lightweight concrete with burden mm		**100**
Edge distance (c) Hollow blocks made of lightweight concrete without burden mm		**250**
Edge distance (c) Full bricks made of lightweight concrete with burden mm		**100**
Edge distance (c) Full bricks made of lightweight concrete without burden mm		**250**

Ташев Галвинг ООД
www.tashev-galving.com

Edge distance (c) aerated concrete with burden mm		**100**
Edge distance (c) aerated concrete without burden mm		**250**
Spacing distance (s) Sandstone mm		**100 / 250 = air rate > 15%**
Spacing distance (s) perforated brick mm		**100 / 250 = air rate > 15%**
Spacing distance (s) Hollow blocks made of lightweight concrete mm		**100 / 250 = air rate > 15%**
Spacing distance (s) aerated concrete mm		**100 / 250 = air rate > 15%**
Additional information		
Weight FS		**2.000 kg**
Type		**10 x 240 / 170**

Ташев-Галвинг ООД
www.tashev-galving.com