

Прекъсвач АВВ автоматичен еднополюсен за DIN шина 1P, 40 А, 230 V, 6 кА, крива С, SH201-C40



General Information

Extended Product Type: S201-C40

Product ID:
2CDS251001R0404

EAN:
4016779464802

Catalog Description:
Miniature Circuit Breaker - S200 - Number of Poles 1 - Tripping characteristic C

Long Description:

System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space.

EAN:
4016779464802

Minimum Order Quantity:
1 piece

Customs Tariff Number:
85362010

Dimensions

Product Net Width:
17.5 mm

Product Net Depth:
69.0 mm

Product Net Height:
88.0 mm

Product Net Weight:
0.125 kg

Container Information

Package Level 1 Units:
10 piece

Package Level 1 Width:

92.0 mm

Package Level 1 Length:

183.0 mm

Package Level 1 Height:

80.0 mm

Package Level 1 Gross Weight:

1.295 kg

Package Level 1 EAN:

4016779607117

Environmental

Ambient Air Temperature: Operation -

25 ... +55 °C Storage -40 ... +70 °C

Resistance to Shock acc. to IEC 60068-2-27:

25g / 2 shocks / 13 ms

Resistance to Vibrations acc. to IEC 60068-2-6:

5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In

Environmental Conditions:

28 cycles

with 55 °C / 90-96 %

and 25 °C / 95-100 %

RoHS Status:

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical

Standards:

IEC/EN 60898-1

IEC/EN 60947-2

UL 1077

Number of Poles:

1

Tripping Characteristic:

C

Rated Current (I_n):

40.00 A

Rated Operational Voltage:

acc. to IEC60898-1 230 / 400 V AC acc. to

IEC60947-2 230 V AC **Power Loss:**

4.8 W

Per Pole 4.8 W

Rated Insulation Voltage (U_i): acc. to

IEC/EN 60664-1 440 V **Operational**

Voltage:

Maximum (incl. tolerance) 253 V AC Maximum

(incl. tolerance) 72 V DC Minimum 12 V AC / 12

V DC

Rated Frequency (f):

50 Hz

60 Hz

Rated Short-Circuit Capacity (I_{cn}

):

6 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):

10 kA

Rated Service Short-Circuit Breaking Capacity (I_{cs}):

7.5 kA

Energy Limiting Class:

3

Overvoltage Category:

III

Pollution Degree:

3

Rated Impulse Withstand Voltage (U_{imp}):

4 kV

(6.2 kV @ sea level) kV (5.0 kV @

2000 m) kV **Dielectric Test Voltage:**

50 / 60 Hz, 1 min: 2 kV

Housing Material:

Insulation group II, RAL 7035

Actuator Type:

Insulation group II, black, sealable

Actuator Marking:

I / O

Contact Position Indication:

Red ON / Green OFF Degree of

Protection: IP20**Remarks:**

IP40 in enclosure with cover

Electrical Endurance:

10000 AC cycle

Mechanical Endurance:20000 cycle **Terminal Type:**

Screw Terminals

Screw Terminal Type:

Failsafe Bi-directional Cylinder-lift Terminal

Connecting Capacity:Busbar 10 / 10 mm²Flexible with Ferrule 0.75 ... 25 mm²Flexible 0.75 ... 25 mm²Rigid 0.75 ... 35 mm²Stranded 0.75 ... 35 mm²**Tightening Torque:**

2.8 N·m

Recommended Screw Driver:

Pozidriv 2

Mounting on DIN Rail:

TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Mounting Position:

Any

Technical UL/CSA**Maximum Operating Voltage UL/CSA:**

277 V AC

Connecting Capacity UL/CSA:

Busbar 18 ... 8 AWG Conductor 18 ... 4

AWG Tightening Torque UL/CSA:

25 in·lb

Interrupting Rating acc. to UL1077:

6 kA

Продукт: [Прекъсвач ABB автоматичен еднополюсен за DIN шина 1P, 40 A, 230 V, 6 kA, крива C, SH201-C40](#)

Категория: [Прекъсвачи миниатюрни автоматични](#)

Бранд: [ABB](#)

Категория бранд: [Прекъсвач ABB](#)