

416-C6



General Information

Extended Product Type:

416-C6

Product ID:

2CMA193526R1000

EAN:

7392696935265

Catalog Description:

Connector, 6h, 16A, IP44, 3P+N+E

Long Description:

Connector, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, 50 - 60 Hertz, color code red

Categories

Products»

- Low Voltage Products and Systems
 - »
- Industrial Plugs and Sockets
 - »
- Plugs & Sockets
 - »
- Connectors

Ordering

EAN:

7392696935265

Minimum Order Quantity:

10 piece

Country of Origin:

Czech Republic (CZ)

Dimensions

Product Net Width:

90 mm

Product Net Height:

90 mm

Product Net Length:

154 mm

Product Net Depth:

90 mm

Product Net Weight:

0.225 kg

Container Information

Package Level 1 Width:

158 mm

Package Level 1 Length:

138 mm

Package Level 1 Height:

345 mm

Package Level 1 Gross Weight:

0.225 kg

Package Level 1 EAN:

7392696935265

Package Level 1 Units:

10 piece

Environmental**RoHS Status:**

Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-03-01

Certificates and Declarations (Document Number)**Declaration of Conformity - CE:**

2CMC700005D0001

Environmental Information:

2CMC700001D0002

RoHS Information:

2CMC700057D0001

Additional Information**Additional Information:**

Cable entry, compression gland

Cable Cross-Section:

1.0 ... 2.5 mm²

Color:

Red

Degree of Protection:

IP44

Enclosure Material:

Polyamide

Frequency (f):

50 Hz

60 Hz

Function:

Connector

IIT Publishing Status:

Level 0 - Information enabled

Invoice Description:

Ind. P&S#416-C6

Number of Poles:

5

Object Classification Code:

2CMT005069

Product Main Type:

C

Product Name:

Industrial Connector

Protection Type:

Splashproof

Rated Current (I_n):

16 A

Rated Voltage (U_r):

346 ... 415 V

RoHS Date:

L23

Standards:

IEC 60309-1,-2

Suitable For:

Connectors

Suitable for Product Class:

Industrial Plugs and Sockets