

416RS6



General Information

Extended Product Type:

416RS6

Product ID:

2CMA193115R1000

EAN:

7392696931151

Catalog Description:

Surface socket-outlet, 6h, 16A, IP44, 3P+N+E

Long Description:

Surface socket-outlet, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Categories

Products»

- Low Voltage Products and Systems

»

- Industrial Plugs and Sockets

»

- Plugs & Sockets

»

- Surface Socket Outlets

Ordering

EAN:

7392696931151

Minimum Order Quantity:

10 piece

Country of Origin:

Czech Republic (CZ)

Dimensions

Product Net Width:

79 mm

Product Net Height:

132 mm

Product Net Length:

100 mm

Product Net Depth:

132 mm

Product Net Weight:

0.26 kg

Container Information

Package Level 1 Width:

143 mm

Package Level 1 Length:

397 mm

Package Level 1 Height:

187 mm

Package Level 1 Gross Weight:

0.26 kg

Package Level 1 EAN:

7392696931151

Package Level 1 Units:

10 piece

Environmental

RoHS Status:

Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-03-01

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:

2CMC700005D0001

Environmental Information:

2CMC700001D0002

RoHS Information:

2CMC700057D0001

Additional Information

Additional Information:

Cable entry, flexible membrane and metric threaded M20 insert for top cable entry. Rear knock-out cable entry.

Cable Cross-Section:

1.5 ... 4 mm²

Color:

Red

Degree of Protection:

acc. to IEC 60529 IP44

Enclosure Material:

Thermoplastic

Frequency (f):

50 Hz

60 Hz

Function:

Surface socket outlet

IIT Publishing Status:

Level 0 - Information enabled

Invoice Description:

Ind. P&S#416RS6

Number of Poles:

5

Object Classification Code:

2CMT005069

Product Main Type:

RS

Product Name:

Industrial Socket Outlet

Protection Type:

Splashproof

Rated Current (I_n):

16 A

Rated Voltage (U_r):

346 ... 415 V

RoHS Date:

L23

Standards:

IEC 60309-1,-2

Suitable For:

Surface Socket Outlets

Suitable for Product Class:

Ташев-Галвинг ООД
www.tashev-galving.com