

### **General Information**

Extended Product Type: 216R6

 Product ID:
 2CMA193146R1000

 EAN:
 7392696931465

**Catalog Description:** Socket-outlet, panel mounting, 6h, 16A, IP44, minimized flange, straight, 2P+E **Long Description:** Socket Outlet Panel Mounting, earthing sleeve position 6h, rated current 16A, IP4

Socket Outlet Panel Mounting, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Blue

## **Categories**

Products » Low Voltage Products and Systems » Industrial Plugs and Sockets » Plugs & Sockets » Socket Outlets for Panel Mounting

## Ordering

EAN: 7392696931465 Minimum Order Quantity: 10 piece

Country of Origin: Czech Republic (CZ)

### **Dimensions**

Product Net Width:56 mmProduct Net Height:85 mmProduct Net Length:73 mmProduct Net Depth:85 mmProduct Net Weight:0.23 kg

#### **Container Information**

Package Level 1 Width:131 mmPackage Level 1 Length:227 mmPackage Level 1 Height:117 mmPackage Level 1 Gross Weight:0.23 kgPackage Level 1 EAN:7392696931465Package Level 1 Units:10 piece

## **Environmental**

RoHS Status: Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-03-

# Certificates and Declarations (Document Number)

Declaration of Conformity - CE:2CMC700005D0001Environmental Information:2CMC700001D0002RoHS Information:2CMC700057D0001

#### **Additional Information**

Additional Information: Cable entry, flexible membrane and metric threaded M20 insert for top cable entry. Rear

knock-out cable entry.

Cable Cross-Section: 1.5 ... 4 mm<sup>2</sup>

Degree of Protection: IP44

Enclosure Material: Thermoplastic
Frequency (f): 50 Hz
60 Hz

Function: Socket outlet for panel mounting IIT Publishing Status: Level 0 - Information enabled

Invoice Description:Ind. P&S#216R6Mounting Type:minimized flange, straight

Number of Poles: 3

Object Classification Code: 2CMT005069

Product Main Type:

Product Name: Industrial Socket Outlet Panel Mounting

 $\begin{array}{lll} \textbf{Protection Type:} & Splashproof \\ \textbf{Rated Current (I_n):} & 16 \text{ A} \\ \textbf{Rated Voltage (U_r):} & 200 \dots 250 \text{ V} \\ \end{array}$ 

RoHS Date: L23

Standards: IEC 60309-1,-2

Suitable For: Socket Outlets for Panel Mounting Suitable for Product Class: Industrial Plugs and Sockets

### Classifications

E-nummer: 2416603 UNSPSC: 39120000







