

General Information

Extended Product Type: 432RU6

 Product ID:
 2CMA193259R1000

 EAN:
 7392696932592

Catalog Description: Socket-outlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+N+E

Long Description: Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 32A, IP44

splashproof, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code

Red

Categories

Products » Low Voltage Products and Systems » Industrial Plugs and Sockets » Plugs & Sockets » Socket Outlets for Panel Mounting

Ordering

EAN: 7392696932592

Minimum Order Quantity: 10 piece

Country of Origin: Czech Republic (CZ)

Dimensions

Product Net Width: 75 mm
Product Net Height: 104 mm
Product Net Length: 93 mm
Product Net Depth: 104 mm
Product Net Weight: 0.24 kg

Container Information

Package Level 1 Width: 143 mm
Package Level 1 Length: 397 mm
Package Level 1 Height: 187 mm
Package Level 1 Gross Weight: 0.24 kg
Package Level 1 EAN: 7392696932592
Package Level 1 Units: 10 piece

Environmental

RoHS Status: Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-03-

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:2CMC700005D0001Environmental Information:2CMC700001D0002RoHS Information:2CMC700057D0001

Additional Information

 Cable Cross-Section:
 2.5 ... 10 mm²

 Color:
 Red

Degree of Protection: IP44

Enclosure Material: Thermoplastic

Frequency (f): 50 Hz
60 Hz

Function: Socket outlet, panel mounting, unified flange, straight

IIT Publishing Status: Level 0 - Information enabled

Invoice Description:Ind. P&S#432RU6Mounting Type:unified flange, straight

Number of Poles: 5

Object Classification Code: 2CMT005069

Product Main Type: RU

Product Name: Industrial Socket Outlet Panel Mounting

RoHS Date: L23

Standards: IEC 60309-1,-2

Suitable For: Socket Outlets for Panel Mounting

Suitable for Product Class: Industrial Plugs and Sockets

Classifications

E-nummer: 2416660 **UNSPSC**: 39120000





