

Прекъсвач АВВ мощностен автоматичен тип А-2 3Р, 250 А, 690 V, 3.75-37.5 kA, Tmax XT3N 250 TMD 250-2500 3p F F



General Information

Extended Product Type:

XT3N 250 TMD 250-2500 3p F F

Product ID:

1SDA068059R1

EAN:

8015644019303

Catalog Description:

XT3N 250 TMD 250-2500 3p F F

Long Description:

C.BREAKER Tmax XT3N 250 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 250-2500 A

Categories

Ordering

EAN:

8015644019303

Minimum Order Quantity:

1 piece

Customs Tariff Number:

85362090

Dimensions

Product Net Width:

105 mm

Product Net Height:

150 mm

Product Net Depth:

70 mm

Product Net Weight:

1.6 kg

Container Information

Package Level 1 Units:

1 piece

Package Level 1 Width:

155 mm

Package Level 1 Height:

190 mm

Package Level 1 Length:

155 mm

Package Level 1 Gross Weight:

1.7 kg

Package Level 1 EAN:

8015644019303

Additional Information

Circuit Breaker Type to be Associated:

Power distribution

Electrical Durability:

120 cycles per hour

8000 cycle

Mechanical Durability:

Nr. Operations 240 cycles per hour Nr.

Operations 25000 cycle **Number of Poles:**

3

Opening Time:

CB with SOR 15 ms CB with

UVR 15 ms **Power Loss:**

Per Pole 17.8 W **Product Main**

Type: SACE Tmax XT **Product**

Name:

Automatic Circuit Breaker

Product Type:

CB

Rated Current (I_n):

250 A

Rated Frequency (f):

50 / 60 Hz

Rated Impulse Withstand Voltage (U_{imp}):

8 kV

Rated Insulation Voltage (U_i):

800 V

Rated Operational Voltage:

690 V AC

500 V DC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):

(220V AC) 37,5 kA

(220V AC) 37,5 kA (380V AC)

27 kA (415V AC) 27 kA (440V

AC) 18,75 kA (500V AC) 15 kA

(690V AC) 3,75 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):

(220V AC) 50 kA

(230V AC) 50 kA (380V

AC) 36 kA (415V AC) 36 kA

(440V AC) 25 kA (500V

AC) 20 kA (690V AC) 5 kA

(250V DC) 2 poles in series 36 kA (500V DC)

3 poles in series 36 kA **Rated Uninterrupted**

Current (I_u):

250 A

Rated Voltage (U_r):

690 V

Release Type:

TM **Standards:** IEC

60947-2

Sub-type:

XT3

Terminal Connection Type:

Fixed Circuit-Breakers

Version:

F

Certificates and Declarations (Document Number)**Declaration of Conformity - CE:**

1SDL000165R0011

GL Certificate:

1SDL000163R0094

LR Certificate:

1SDL000163R0100

Продукт: [Прекъсвач АВВ мощностен автоматичен тип А-2 3Р, 250 А, 690 V, 3.75-37.5 кА, Tmax XT3N 250 TMD 250-2500 3р F F](#)

Категория: [Мощностни автоматични прекъсвачи](#)

Бранд: [ABB](#)

Категория бранд: [Прекъсвач АВВ](#)

Ташев-Галвинг ООД
www.tashev-galving.com