

## Контактор АВВ модулен автоматичен 2Р, 2 NO, 24 V, 20 A, ESB20-20 24V 50Hz / 28V 60Hz



## ESB20-20 24V 50Hz / 28V 60Hz

ESB20-20 24V 50Hz / 28V 60Hz Installation Contactor



### General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | ESB20-20 24V 50Hz / 28V 60Hz                        |
| Product ID            | GHE3211102R0001                                     |
| EAN                   | 3471520263218                                       |
| Catalog Description   | ESB20-20 24V 50Hz / 28V 60Hz Installation Contactor |
| Long Description      | ESB20-20 24V 50Hz / 28V 60Hz Installation Contactor |

## Ordering

|                        |               |
|------------------------|---------------|
| Package Level 1 EAN    | 3471520263218 |
| Minimum Order Quantity | 10 piece      |
| Customs Tariff Number  | 85364900      |

## Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SAC101101D0201 |
| Instructions and Manuals          | 1SAC101101D0201 |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 17.5 mm |
| Product Net Height         | 86 mm   |
| Product Net Depth / Length | 67 mm   |
| Product Net Weight         | 0.13 kg |

## Technical

|  |   |
|--|---|
| Rated Operational Voltage                | Main Circuit 250 V  |
| Rated Frequency (f)                      | 50 / 60 Hz  |
| Rated Operational Current AC-1 ( $I_e$ ) | for Air Temperature Near the Contactor = 55 °C 20 A   |
| Rated Operational Power AC-1 ( $P_e$ )   | (230 V) Single Phase 4 kW   |
| Rated Insulation Voltage ( $U_i$ )       | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 400 V  |
| Electrical Durability                    | max. 1e AC-3 0.15 million   |
| Mechanical Durability                    | 1 million   |
| Number of Main Contacts NO               | 2   |
| Standards                                | Devices complying with international standards IEC 60 947-4-1 / IEC 1095 and European standards EN 60 |

947-4-1 / EN 61095.

## Environmental

Ambient Air Temperature Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... +55 °C

## Certificates and Declarations (Document Number)

|                                |  |
|--------------------------------|--|
| BV Certificate                 | BV_2634H13153C0                              |
| CB Certificate                 | CB_CN_40722<br>CB_CN_40723                   |
| CCC Certificate                | CCC_2017010304985167<br>CCC_2017010304986116 |
| CEBEC Certificate              | CB_B21_1996_A1-A2                            |
| CSA Certificate                | CSA_1169513                                  |
| cUL Certificate                | UL_20110728-E312527_12_1                     |
| Declaration of Conformity - CE | 1SBD250201U1000                              |
| EAC Certificate                | EAC_RU C-FR ME77 B02896                      |
| Environmental Information      | 1SBD250054E1000                              |
| GOST Certificate               | GOST_POCCFRME77B07175                        |
| Instructions and Manuals       | 1SAC101101D0201                              |
| LOVAG Certificate              | LOVAG_FR96042                                |
| RMRS Certificate               | 1SAA920000-0703                              |
| RoHS Information               | 1SBC101058D0201                              |
| UL Certificate                 | UL_20030401-E39231                           |
| UTE Certificate                | NF_668045-A2                                 |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 10 piece      |
| Package Level 1 Width          | 92 mm         |
| Package Level 1 Height         | 76 mm         |
| Package Level 1 Depth / Length | 183 mm        |
| Package Level 1 Gross Weight   | 1.3 kg        |
| Package Level 1 EAN            | 3471520263218 |
| Package Level 2 Units          | 120 piece     |
| Package Level 2 Gross Weight   | 15.6 kg       |
| Package Level 3 Units          | 2160 piece    |

## Classifications

|                            |  |
|----------------------------|--|
| Object Classification Code | Q  |
| E-nummer                   | 3225001  |
| ETIM 4                     | EC001653 - Installation contactor for distribution board |
| ETIM 5                     | EC001653 - Installation contactor for distribution board |
| ETIM 6                     | EC001653 - Installation contactor for distribution board |
| UNSPSC                     | 39121529   |

Продукт: [Контактор АВВ модулен автоматичен 2Р, 2 NO, 24 V, 20 A, ESB20-20 24V 50Hz / 28V 60Hz](#)

Категория: [Контактори и защитни релета](#)

Бранд: [ABB](#)

Категория бранд: [Контактор АВВ](#)

Ташев-Галвинг ООД  
[www.tashev-galving.com](http://www.tashev-galving.com)