

HOSE PROTECTION



Weldalloy Product Line

Pig's Tail™ Protective Wrapping

Sizes: 15

Internal Diameter Range: 7 mm - 149 mm
External Diameter Range: 9 mm - 160 mm
Helix Width Range: 6.5 mm - 60 mm

Pig's Tail™ protective wrapping is made to protect hydraulic and pneumatic hoses against shocks, abrasion and deteriorations. As cost effectiveness is always a critical consideration, our Pig's Tail™ protective wrapping can help you reduce your maintenance costs and equipment downtime.

Made from High Density Polyethylene* (HDPE) Pig's Tail™ protective wrapping can easily be mounted on existing or new assembled hydraulic hoses, giving them protection against wear and damage caused by aggressive working conditions.

Other advantages of the Pig's Tail™ protective wrapping:

- Can be used for a single hose or a bundle of hoses.
- Suitable for use with equipment operating across a wide temperature range from -50°C up to +120°C.
- Rounded edges for easy and safe mounting.
- Suitable for use with all hydraulic fluids including glycol and phosphate ester based products.
- Free sample requests are for parts listed in chart only

Standard colour is black; also available in yellow, blue, red and green.

Product Code	Internal Diameter (mm)*	External Diameter (mm)*	Wall Thickness (mm)	Pitch	Meters/Box
R9SSG	7	9	1.5	6.50	150
R12SSG	10	12	1.5	10	20/50
R16SSG	11.5	16	1.5	12	20/50
R20SSG	14	20	1.8	14.50	20/50
R25SSG	20	25	2	21	20/50
R32SSG	25	32	2.4	24	20/50
R40SSG	32	40	2.4	30	20/50
R50SSG	38	50	3	35	20/50
R63SSG	50	63	3.5	40	20
R75SSG	60	75	3.8	40	20
R90SSG	72	90	4.6	45	20
R110SSG	87	110	5.5	55	12
R125SSG	114	125	5.5	55	12
R140SSG	129	140	5.5	55	8
R160SSG	149	160	5.5	60	6

* Nominal dimensions



Weldalloy Product Line

Fire Retardant Anti-Static (FRAS)

Sizes: 11

Internal Diameter Range: 10 mm - 87 mm
External Diameter Range: 12.5 mm - 110 mm
Helix Width Range: 10 mm - 55 mm

FRAS Pig's Tail™ protective wrapping is a conductive thermoplastic compound on a polyethylene base. Conductivity is achieved by using special conductive carbon black. In addition to low electrical resistivity, FRAS is flame retardant and has an extremely good balance of mechanical properties.

- Free sample requests are for parts listed in chart only

Tested and certified to:

- AS2600
- AS180.10B
- AS180.13A
- MSHA - approved
- SIMTARS
- ATEX

Product Code	Internal Diameter (mm)*	External Diameter (mm)*	Wall Thickness (mm)	Pitch	Meters/Box
FRAS12-50	10	12	1.5	10	50
FRAS16-20	11.5	16	1.5	12	20
FRAS20-20	14	20	1.8	14.50	20
FRAS25-20	20	25	2	21	20
FRAS32-20	25	32	2.4	24	20
FRAS40-20	32	40	2.4	30	20
FRAS50-20	38	50	3	35	20
FRAS63-20	50	63	3.5	40	20
FRAS75-20	60	75	3.8	40	20
FRAS90-20	72	90	4.6	45	20
FRAS110-12	87	110	5.5	55	12

* Nominal dimensions

Продукт: [Спирала Carlugs предпазна за маркуч 12-16 мм, 50 м, HDPE](#)

Категория: [Предпазни ленти и спирали за маркучи](#)

Бранд: [Carlugs](#)

Категория бранд: [Спирала Carlugs](#)