Motion detector

IS 180-2

EAN 4007841 603212

























manufacture's warranty steinel.de/garantie

Function description

Homeowner's darling. Infrared wall sensor IS 180-2, for indoors an with corner wall mount, 180° angle of coverage, reach can be selfucustomised with shrouds. building fronts and driveways, suitable for corner mounting exable time and twilight threshold, detection zone can be

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	56 x 76 x 120 mm
Mains power supply	230 V / 50 Hz
Sensor Technology	passive intrared
Application, place	Indoors, Outdoors
Installation site	Wall, corner
Installation	Surface wiring
Mounting height	1,80 – 4,00 m
Reach, radial	$r = 1.5 \text{ m } (4 \text{ m}^2) \text{ T} = 3 \text{ m } (14 \text{ m}^2)$
Reach, tangential	$r = 5 \text{ m} (39 \text{ m}^2) / r = 12 \text{ m} (226 \text{ m}^2)$
Detection angle	180°
Angle of aperture	90°
Switching zones	504 switching zones
Optimum mounting height	2 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx

Time setting	5 s – 15 Min.
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs fluorescent lamps	[/] 6 pcs.
Capacitive load in µF	132 μF
Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	white
PU1, EAN	4007841603212

Motion detector

IS 180-2

EAN 4007841 603212



Detection Zone

2 m 12 m

Mögliche Montagehöhe: 1,80 m – 4,00 m

Orange: radial Schwarz: tangential

Dimension Drawing

