

Motion detector

IS 2360 ECO

EAN 4007841006556



Function description

Elegant. Compact. Inconspicuous. IS 2360 ECO precision infrared surface-mounted sensor. Ideal for porches and small rooms. 360° angle of coverage, 160° angle of aperture and 7 m reach. Includes shrouds for customising the detection zone. Passive infrared sensor technology. Easy to install. Finish colour: white.

Technical specifications

Type	Motion detectors
Dimensions (Ø x H)	115 x 50 mm
Mains power supply	230 V / 50 – 60 Hz
Sensor Technology	passive infrared
Application, place	outdoors, indoors
Application, place, room	corridor, aisle, side room, equipment room, warehouse
Installation site	ceiling
Type of installation	Surface wiring
Switching zones	664 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,00 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Reach, radial	Ø 3 m (7 m ²)
Reach, tangential	Ø 7 m (38 m ²)

Motion detector

IS 2360 ECO

EAN 4007841006556

Technical specifications

Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Switching output 1, resistive	2000 W
Switching output 1, number of LEDs / fluorescent lamps	6 pcs.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
IDs, certificates	VDE
Manufacturer's Warranty	5 years
PU1, EAN	4007841006556

Ташев-Галвинг ООД
www.tashev-galving.com