


Presence detector - Professional Line

DualTech

DALI-2 Input Device
EAN 4007841 057473
Article number 057473



Function description

The best of both worlds. Combined in one detector. Ultrasonic presence detector DualTech, ideal for offices, conference rooms and class rooms. 36 sq.m. presence zone, ultrasonic technology provides reliable detection behind objects regardless of temperature, additional detection capability with PIR technology. DALI-2 Input Device enables sensors to communicate collected sensor data to higher-level lighting management systems.

Type	Presence detector	Sneak-by guard	Yes
Dimensions (L x W x H)	66 x 120 x 120 mm	Capability of masking out individual segments	No
Mains power supply	12 – 22,5 V	Electronic scalability	Yes
Power supply, detail	DALI bus	Twilight setting TEACH	No
Number of Dali users	12	Twilight setting	10 – 1000 lx
Sensor Technology	Ultrasonic	Control output, Dali	Addressable/slave
Application, place	Indoors	Constant-lighting control	No
Installation site	ceiling	Basic light level function	No
Installation	Concealed wiring	Settings via	Bus
Mounting height	2,50 – 3,5 m	With remote control	No
Reach, radial	Ultrasonic: Ultraschall: Ø 10 m (Ultraschall: 79 m ²)	Interconnection	Yes
Reach, tangential	Ultrasonic: Ultraschall: Ø 10 m (Ultraschall: 79 m ²)	Type of interconnection	Master/slave
Reach, presence	Ultrasonic: Ultraschall: Ø 6 m (Ultraschall: 28 m ²)	IP-rating	IP20
Sensor Technology 2	passive infrared	Material	Plastic
Reach, radial 2	passive infrared: Passiv Infrarot: Ø 4 m (Passiv Infrarot: 13 m ²)	Ambient temperature	-25 – +55 °C
Reach, tangential 2	passive infrared: Passiv Infrarot: Ø 8 m (Passiv Infrarot: 50 m ²)	Application, room	classroom, one-person office, open-plan office, conference room / meeting room, duty room, recreation room, Indoors
Reach, presence 2	passive infrared: Passiv Infrarot: Ø 4 m (Passiv Infrarot: 13 m ²)	Colour	white
Ultrasonic technology	40 kHz	Colour, RAL	9010
Detection angle	360 °	Manufacturer's Warranty	5 years
Angle of aperture	180 °	Version	DALI-2 Input Device
Optimum mounting height	2,8 m	PU1, EAN	4007841057473
Mechanical scalability	No		


Presence detector - Professional Line

DualTech

DALI-2 Input Device
 EAN 4007841 057473
 Article number 057473




Detection Zone



Mögliche Montagehöhe: 2,50 m – 3,50 m
 Orange: Präsenz und tangential
 Schwarz: radial

Dimension Drawing



Circuit diagram

