


Presence detector - Professional Line

DualTech

V3 KNX - Concealed wiring
EAN 4007841 059521
Article number 059521



Function description

The best of both worlds. Combined in one detector. Ultrasonic presence detector DualTech KNX, ideal for offices, conference rooms and class rooms. 36 sq.m. presence zone, ultrasonic technology provides reliable detection behind objects regardless of temperature, additional detection capability with PIR technology, electronic adjustment for ultrasonic reach, with digital BUS interface for controlling 4 lighting channels and HVAC.

Technical specifications

Dimensions (L x W x H)	65 x 120 x 120 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	No
Version	KNX - Concealed wiring
PU1, EAN	4007841059521
Type	Presence detector
Application, place	Indoors
Application, room	classroom, one-person office, open-plan office, conference room / meeting room, duty room, recreation room, Indoors
Colour	white
Colour, RAL	9010
Includes corner wall mount	No
Installation site	ceiling

Mounting height max.	3,50 m
Optimum mounting height	2,8 m
Ultrasonic technology	40 kHz
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ultrasonic: Ultraschall: Ø 10 m (Ultraschall: 79 m ²)
Reach, tangential	Ultrasonic: Ultraschall: Ø 10 m (Ultraschall: 79 m ²)
Reach, presence	Ultrasonic: Ultraschall: Ø 6 m (Ultraschall: 28 m ²)
Twilight setting	10 – 1000 lx
Time setting	10 s – 1092 Min.

Presence detector - Professional Line

DualTech

V3 KNX - Concealed wiring
 EAN 4007841 059521
 Article number 059521




Technical specifications

Installation	Concealed wiring, Ceiling	Basic light level function	Yes
IP-rating	IP20	Basic light level function time	1-255 min
Ambient temperature	-25 – 55 °C	Main light adjustable	0 - 100 %
Material	Plastic	Twilight setting TEACH	Yes
Mains power supply	30 V	Constant-lighting control	Yes
Power consumption	0,7 W	KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
Power supply, detail	KNX bus	Interconnection	Yes
With bus coupling	Yes	Type of interconnection	Master/master, Master/slave
Sensor Technology 2	passive infrared	Interconnection via	KNX bus
Technology, sensors	Ultrasonic, passive infrared, Light sensor	Rated current	17,5 mA
Mounting height	2,50 – 3,5 m		

Accessories

EAN 4007841 002855	Clamping-type ceiling adapter Control PRO UP Box
EAN 4007841 000363	Surface-mounted adapter Control Pro IP54
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

Detection Zone



Possible mounting height: 2,50 m – 3,50 m
 Orange: presence and tangential
 Black: radial

Dimension Drawing

