

Прекъсвач АВВ автоматичен еднополюсен за DIN шина 1P, 16 A, 230 V, 6 kA, крива C, S201-C16



General Information Extended

Product Type: S201-C16

Product ID:

2CDS251001R0164

EAN:

4016779464406

Catalog Description:

Miniature Circuit Breaker - S200 - 1P - C - 16 A Long

Description:

System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs

of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space. Categories

Products»

»

▢ Modular DIN Rail Products

»

▢ Miniature Circuit Breakers MCBs

Ordering

EAN:

4016779464406

Minimum Order Quantity:

1 piece

Customs Tariff Number:

85362010

Dimensions

Product Net Width:

17.5 mm

Product Net Depth:

69 mm

Product Net Height:

88 mm

Product Net Weight:

0.125 kg

Container Information

Package Level 1 Units:

10 piece

Package Level 1 Width:

92 mm

Package Level 1 Length:

183 mm

Package Level 1 Height:

80 mm

Package Level 1 Gross Weight:

1.295 kg

Package Level 1 EAN:

4016779606882

Package Level 2 Units:

120 piece

Package Level 2 Width:

275 mm

Package Level 2 Length:

395 mm

Package Level 2 Height:

210 mm

Package Level 2 Gross Weight:

14.8 kg

Package Level 2 EAN:

4016779970723

Environmental

Ambient Air Temperature: Operation -25

... +55 °C Storage -40 ... +70 °C

Resistance to Shock acc. to IEC 60068-2-27:

25g / 2 shocks / 13 ms

Resistance to Vibrations acc. to IEC 60068-2-6:

5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In

Продукт: [Прекъсвач АВВ автоматичен еднополюсен за DIN шина 1P, 16 A, 230 V, 6 kA, крива C, S201-C16](#)

Категория: [Прекъсвачи миниатюрни автоматични](#)

Бранд: [ABB](#)

Категория бранд: [Прекъсвач АВВ](#)