

Прекъсвач АВВ автоматичен еднополюсен за DIN шина 1P, 40 A, 230 V, 6 kA, крива C, S201-C40



General Information Extended

Product Type: S201-C40

Product ID:

2CDS251001R0404

EAN:

4016779464802

Catalog Description:

Miniature Circuit Breaker - S200 - 1P - C - 40 A Long

Description:

System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs

of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 and CSA

22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space. Categories

Products»

□ Low Voltage Products and Systems

»

□ Modular DIN Rail Products

»

Ordering

EAN:

4016779464802

Minimum Order Quantity:

1 piece

Customs Tariff Number:

85362010

Dimensions

Product Net Width:

17.5 mm

Product Net Depth:

69 mm

Product Net Height:

88 mm

Product Net Weight:

0.125 kg

Container Information

Package Level 1 Units:

10 piece

Package Level 1 Width:

92 mm

Package Level 1 Length:

183 mm

Package Level 1 Height:

80 mm

Package Level 1 Gross Weight:

1.295 kg

Package Level 1 EAN:

4016779607117

Package Level 2 Units:

120 piece

Package Level 2 Width:

275 mm

Package Level 2 Length:

395 mm

Package Level 2 Height:

210 mm

Package Level 2 Gross Weight:

14.8 kg

Package Level 2 EAN:

4016779970976

Environmental

Ambient Air Temperature: Operation -25

... +55 °C Storage -40 ... +70 °C

Resistance to Shock acc. to IEC 60068-2-27:

25g / 2 shocks / 13 ms

Resistance to Vibrations acc. to IEC 60068-2-6:

5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In

Environmental Conditions:

28 cycles

with 55 °C / 90-96 % and 25 °C /

95-100 % RoHS Status:

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical Standards: IEC/EN

60898-1

IEC/EN 60947-2

UL 1077

Number of Poles:

1

Tripping Characteristic: C

Rated Current (I_n):

40 A

Rated Operational Voltage:
acc. to IEC60898-1 230 / 400 V AC acc. to
IEC60947-2 230 V AC Power Loss:
4.8 W
at Rated Operating Conditions per Pole 4.8 W Rated
Insulation Voltage (U_i):
acc. to IEC/EN 60664-1 440 V
Operational Voltage:
Maximum (Incl. Tolerance) 253 V AC Maximum (Incl.
Tolerance) 72 V DC Minimum 12 V AC / 12 V DC
Rated Frequency (f):
50 Hz
60 Hz
Rated Short-Circuit Capacity (I_{cn}):
6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):
10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs}):
7.5 kA
Energy Limiting Class:
3
Overvoltage Category: III
Pollution Degree:
3
Rated Impulse Withstand Voltage (U_{imp}):
4 kV
(6.2 kV @ sea level) (5.0 kV @ 2000
m) Dielectric Test Voltage:
50 / 60 Hz, 1 min: 2 kV Housing
Material:
Insulation Group II, RAL 7035
Actuator Type:
Insulation group II, black, sealable
Contact Position Indication: Red ON /
Green OFF Degree of Protection:
IP20
Remarks:
IP40 in enclosure with cover
Electrical Endurance:
10000 AC cycle
Mechanical Endurance:
20000 cycle Terminal Type:
Screw Terminals
Screw Terminal Type:
Failsafe Bi-directional Cylinder-lift Terminal
Connecting Capacity:
Busbar 10 / 10 mm²
Flexible with Ferrule 0.75 ... 25 mm²
Flexible 0.75 ... 25 mm²
Rigid 0.75 ... 35 mm²
Stranded 0.75 ... 35 mm²
Tightening Torque:
2.8 N·m
Recommended Screw Driver: Pozidriv 2
Mounting on DIN Rail:
TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position: Any
Technical UL/CSA
Maximum Operating Voltage UL/CSA:
277 V AC
Connecting Capacity UL/CSA: Busbar 18 ... 8
AWG Conductor 18 ... 4 AWG Tightening
Torque UL/CSA:
25 in·lb

Interrupting Rating acc. to UL1077:

6 kA

Certificates and Declarations (Document Number) Declaration of
Conformity - CE:

2CDK403001D0602

RoHS Information:

2CDK400003K0201

Classifications eClass:

7.0 27141901

E-nummer:

2100528

ETIM 4.0:

EC000042 - Miniature circuit breaker (MCB) ETIM 5.0:

EC000042 - Miniature circuit breaker (MCB)

Продукт: [Прекъсвач АВВ автоматичен еднополюсен за DIN шина 1P, 40 A, 230 V, 6 kA, крива C, S201-C40](#)

Категория: [Прекъсвачи миниатюрни автоматични](#)

Бранд: [ABB](#)

Категория бранд: [Прекъсвач АВВ](#)

Ташев-Галвинг ООД
www.tashev-galving.com