S203-C6



General Information
Extended Product Type:
S203-C6
Product ID:
2CDS253001R0064
EAN:
4016779467506
Catalog Description:
Miniature Circuit Breaker - S200 - 3P - C - 6 A
Long Description:
System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space.
Categories

Products»

- Low Voltage Products and Systems

  »

- Modular DIN Rail Products

  »

- Miniature Circuit Breakers MCBs

Accessories Show accessory images
Ordering

Ташев галвинг ООД
www.tashev-galving.com

EAN:
4016779467506
Minimum Order Quantity:
1 piece
Customs Tariff Number:
85362010
Dimensions
Product Net Width:
52.5 mm
Product Net Depth:
69 mm
Product Net Height:
88 mm
Product Net Weight:
0.375 kg
Container Information
Package Level 1 Units:
1 piece
Package Level 1 Width:
92 mm
Package Level 1 Length:
58 mm
Package Level 1 Height:
80 mm
Package Level 1 Gross Weight:
0.4 kg
Package Level 1 EAN:
4016779609067
Package Level 2 Units:
36 piece
Package Level 2 Width:
275 mm
Package Level 2 Length:
395 mm
Package Level 2 Height:
210 mm
Package Level 2 Gross Weight:
13.36 kg
Package Level 2 EAN:
4016779973045
Environmental
Ambient Air Temperature:
Operation -25 ... +55 °C
Storage -40 ... +70 °C
Resistance to Shock acc. to IEC 60068-2-27:
25g / 2 shocks / 13 ms
Resistance to Vibrations acc. to IEC 60068-2-6:
5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Environmental Conditions:
28 cycles

Гашев-Галвинг ООД
www.tashev-galving.com

with 55 °C / 90-96 %
and 25 °C / 95-100 %
RoHS Status:
Following EU Directive 2002/95/EC August 18, 2005 and amendment
Technical
Standards:
IEC/EN 60898-1
IEC/EN 60947-2
UL 1077
Number of Poles:
3
Tripping Characteristic:
C
Rated Current (I_n):
6 A
Rated Operational Voltage:
acc. to IEC60898-1 400 V AC
acc. to IEC60947-2 440 V AC
Power Loss:
6 W
at Rated Operating Conditions per Pole 2 W
Rated Insulation Voltage (U_i):
acc. to IEC/EN 60664-1 440 V
Operational Voltage:
Maximum (Incl. Tolerance) 440 V AC
Minimum 12 V AC / 12 V DC
Rated Frequency (f):
50 Hz
60 Hz
Rated Short-Circuit Capacity (I_{cn}):
6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):
10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs}):
7.5 kA
Energy Limiting Class:
3
Overvoltage Category:
III
Pollution Degree:
3
Rated Impulse Withstand Voltage (U_{imp}):
4 kV
(6.2 kV @ sea level)
(5.0 kV @ 2000 m)
Dielectric Test Voltage:
50 / 60 Hz, 1 min: 2 kV
Housing Material:
Insulation Group II, RAL 7035
Actuator Type:

Ташев-Галвинг ООД
www.tashev-galving.com

Insulation group II, black, sealable
Contact Position Indication:
Red ON / Green OFF
Degree of Protection:
IP20
Remarks:
IP40 in enclosure with cover
Electrical Endurance:
20000 AC cycle
Mechanical Endurance:
20000 cycle
Terminal Type:
Screw Terminals
Screw Terminal Type:
Failsafe Bi-directional Cylinder-lift Terminal
Connecting Capacity:
Busbar 10 / 10 mm²
Flexible with Ferrule 0.75 ... 25 mm²
Flexible 0.75 ... 25 mm²
Rigid 0.75 ... 35 mm²
Stranded 0.75 ... 35 mm²
Tightening Torque:
2.8 N·m
Recommended Screw Driver:
Pozidriv 2
Mounting on DIN Rail:
TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position:
Any
Technical UL/CSA
Maximum Operating Voltage UL/CSA:
480Y / 277 V AC
Connecting Capacity UL/CSA:
Busbar 18 ... 8 AWG
Conductor 18 ... 4 AWG
Tightening Torque UL/CSA:
25 in·lb
Interrupting Rating acc. to UL1077:
6 kA
Certificates and Declarations (Document Number)
Declaration of Conformity - CE:
2CDK403001D0602
RoHS Information:
2CDK400003K0201
Classifications
eClass:
7.0 27141901
E-nummer:
2100592

Гашев-Галвинг ООД
www.tashev-galving.com

ETIM 4.0:
EC000042 - Miniature circuit breaker (MCB)
ETIM 5.0:
EC000042 - Miniature circuit breaker (MCB)
Object Classification Code:
F

Ташев-Галвинг ООД
www.tashev-galving.com