

Дефектнотокова защита Schneider Electric 2P тип AC 63 A, 30 mA, 2P, 10 kA, Acti 9 iID



Main

Range of product	ID RCCB
Device short name	ID RCCB
Poles description	2P
Neutral position	Left
[In] rated current	63 A
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class AC
Rated breaking and making capacity	Im 1500 A conforming to IEC 61008

Utilisation category	AC-23A conforming to IEC 60947-3
9 mm pitches	4

Complementary

Rated conditional short-circuit current	Inc 10 kA 63 A
[Ui] rated insulation voltage	440 V conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-3
Product weight	0.23 kg
Mechanical durability	20000
cycles Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminals 35 mm² flexible Tunnel type terminals 50 mm² rigid

Environment

Standards	IEC 60947-1 IEC 60947-3 IEC 61008
Tropicalisation	2
Relative humidity	95 % (55 °C
) Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-40...60 °C
RoHS EUR status	Will be compliant

Продукт: [Дефектнотокова защита Schneider Electric 2P тип AC 63 A, 30 mA, 2P, 10 kA, Acti 9 iLD](#)

Категория: [Дефектнотокова защита](#)

Бранд: [Schneider Electric](#)

Категория бранд: [Дефектнотокова защита Schneider Electric](#)