Photo-cell controller

NightMatic 3000 Vario

black

EAN 4007841 550516

Twilight switch + eco-mode | 1000 W max. (LED-ready) | IP54 | 0,5 - 10 lux | energy saving | manufacture's warranty steinel.de/garantie | CE | TüV Nord Baumuster checked

Function description

Intelligent lighting control. Photo-electric lighting controller NightMatic 3000 VARIO, for controlling lighting systems for building fronts, properties, shop windows etc., automatically switches light 'ON' at dusk automatically 'OFF' again at dawn, with selectable night economy mode.

Technical specifications

Type	Photo-cell controller
Dimensions (L x W x H)	37 x 74 x 99 mm
Mains power supply	230 – 240 V / 50 Hz
Power consumption	0,8 W
Sensor Technology	Light sensor
Application, place	Outdoors
Installation site	wall
Installation	Surface wiring
Twilight setting TEACH	Yes
Twilight setting	0,5 – 10 lx
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	4 pcs.
Capacitive load in µF	88 µF
Constant-lighting control	No

Basic light level function	No
Functions	Night economy mode, light ON / OFF in the morning
Settings via	Potentiometers
Interconnection	Yes
Type of interconnection	Master/master
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	black
Colour, RAL	9005
Manufacturer's Warranty	3 years
Version	black
PU1, EAN	4007841550516

Ташев-Галвинг ООД
www.tashev-galving.com

Photo-cell controller

NightMatic 3000 Vario

black

EAN 4007841 550516

Dimension Drawing



Ташев-Галвинг ООД
www.tashev-galving.com