

Leonardo - UPS устройство непрекъсваемо токозахранващо

| UPS Type | T * | T * | RT (2U) *** | RT (4U) ** | RT (3U) *** | |
|---|---|-------------|--------------|------------------|-------------|------------------|
| Rating (kVA) | 6 | 10 | 6 | 6 | 10 | |
| Nominal Power (kW) | 5.4 | 9 | 5.4 | 5.4 | 9 | |
| UPS dimensions WxDxH (mm) | 290x645x748 | 290x645x748 | 440x680x88 | 440x680x176 | 440x680x132 | |
| UPS weight (kg) | 86 | 96 | 24 | 52 | 26 | |
| Input | | | | | | |
| Connection type | Hardwired 2w (rectifier), 2w (bypass) | | Hardwired 2w | | | |
| Nominal voltage | 230 Vac 1-phase | | | | | |
| Voltage range | 160 to 280 Vac | | | | | |
| Frequency and range | 50/60 Hz, 45 to 65 Hz | | | | | |
| Power factor | 0.99 | | | | | |
| Current distortion (THDi) | <6% | | | | | |
| Output | | | | | | |
| Connection type | Hardwired 2w | | | | | |
| Nominal voltage | 230 Vac +/-1% 1-phase | | | | | |
| Frequency | 50/60 Hz | | | | | |
| Power factor | Up to 0.9, without power derating | | | | | |
| Overload capability | 104% continuous, 150% for 160 seconds, >150% transfer to bypass | | | | | |
| Mode of operation | On-line, Eco mode | | | | | |
| Classification by IEC/EN 62040-3 | VFI-SS-11 | | | | | |
| Battery | | | | | | |
| Autonomy time internal battery (min.) | 50% load | 25 | 17 | external battery | 15 | external battery |
| | 100% load | 9 | 6 | external battery | 6 | external battery |
| Connectivity and function extensions | | | | | | |
| Front panel | Display LCD, status LED, function keys | | | | | |
| Communication | Included: USB, RS232 card, EPO. Optional: dry contact card, SNMP card, RS485 card. Compatible platforms: Windows, Linux, Mac | | | | | |
| Environmental | | | | | | |
| Operating temperature range | 0°C to +40°C | | | | | |
| Altitude (AMSL) | < 1000 m without power reduction, > 1000 m with reduction of 0.5% per 100 m | | | | | |
| Audible noise at 1 m (dBA) | < 50 | | | | | |
| Standards and certifications | | | | | | |
| Quality assurance, environment, health and safety | ISO 9001:2015, ISO 14001:2015, BS OHSAS 18001:2007 | | | | | |
| Safety | IEC/EN 62040-1 | | | | | |
| EMC | IEC/EN 62040-2 | | | | | |
| Marking | CE | | | | | |

*Tower with internal battery **Rack/Tower with internal battery ***Rack/Tower without internal battery

◇ Measurement conditions: optimised parameters, fully charged battery, 0.7 PF