

## Galileo - UPS устройство непрекъсваемо токозахранващо

| UPS Type   | T *   | T *                       | T *                       | RT (2U)**     | RT (2U)**     | RT (2U)**  |    |
|--|---|---------------------------|---------------------------|---------------|---------------|------------|----|
| Rating (VA)  | 1000  | 2000                      | 3000                      | 1000          | 2000          | 3000       |    |
| Nominal power (W)                                    | 900   | 1800                      | 2700                      | 900           | 1800          | 2700       |    |
| UPS dimensions WxDxH (mm)                            | 144x367x236   | 151x444x322               | 189x444x322               | 440x390x88    | 440x475x88    | 440x600x88 |    |
| UPS weight (kg)                                      | 11.2  | 18.8                      | 24.9                      | 12.0          | 17.0          | 26.5       |    |
| <b>Input</b>   |   |                           |                           |               |               |            |    |
| Connection type                                      | 1 IEC 320-C14   |                           |                           |               |               |            |    |
| Nominal voltage                                      | 230 Vac single phase  |                           |                           |               |               |            |    |
| Voltage range  | 195÷260 Vac   |                           |                           |               |               |            |    |
| Frequency and range                                  | 50/60 Hz, 45÷65 Hz  |                           |                           |               |               |            |    |
| Power factor   | 0.98  |                           |                           | 0.99          |               |            |    |
| Current distortion (THDi)                            | <3%   |                           |                           |               |               |            |    |
| <b>Output</b>  |   |                           |                           |               |               |            |    |
| Connection type                                      | 3 IEC 320-C13<br>1 Schuko   | 3 IEC 320-C13<br>2 Schuko | 6 IEC 320-C13<br>2 Schuko | 3 IEC 320-C13 | 6 IEC 320-C13 |            |    |
| Nominal voltage                                      | 230 Vac +/-1% single phase  |                           |                           |               |               |            |    |
| Frequency  | 50/60 Hz  |                           |                           |               |               |            |    |
| Power factor   | Any power factor up to 0.9 lagging or leading without power derating  |                           |                           |               |               |            |    |
| Overload capability                                  | 105% continuous, 106-120% for 30 seconds, 121-150% for 10 seconds, >150% immediately transfer to bypass                                     |                           |                           |               |               |            |    |
| Mode of operation                                    | On-line, Eco mode   |                           |                           |               |               |            |    |
| <b>Battery</b>                                       |   |                           |                           |               |               |            |    |
| Autonomy time<br>internal battery (min)◆             | 50% load  | 12                        | 13                        | 15            | 12            | 13         | 15 |
|  | 100% load   | 6                         | 6                         | 6             | 6             | 6          | 6  |
| <b>Connectivity and function extensions</b>          |   |                           |                           |               |               |            |    |
| Front panel  | Display LCD, LED signaling, function keys   |                           |                           |               |               |            |    |
| Communication  | Included: USB, EPO<br>Optional: RS485 card, dry contact card, SNMP card, RS232 card.<br>Compatible platforms: Microsoft Windows, Linux, Mac |                           |                           |               |               |            |    |
| <b>Environmental</b>                                 |   |                           |                           |               |               |            |    |
| Operating temperature range                          | 0°C ÷ +40°C   |                           |                           |               |               |            |    |
| Altitude (AMSL)                                      | < 1000 m without power reduction, > 1000 with reduction of 0.5% per 100 m   |                           |                           |               |               |            |    |
| Audible noise at 1m (dBA)                            | <50   |                           |                           |               |               |            |    |
| Relative humidity                                    | 0-90%   |                           |                           |               |               |            |    |
| <b>Standards and certifications</b>                  |   |                           |                           |               |               |            |    |
| Marking  | CE  |                           |                           |               |               |            |    |
| Safety   | IEC/EN 62040-1  |                           |                           |               |               |            |    |
| EMC  | IEC/EN 62040-2  |                           |                           |               |               |            |    |
| Quality assurance,<br>Environment, Health and Safety | ISO 14001:2004, BS OHSAS 18001:2007   |                           |                           |               |               |            |    |

\*Tower \*\*Rack/Tower ◆ Measurement conditions: optimised parameters, battery full charged, Power Factor (PF) 0.7