

Giotto - UPS устройство непрекъсваемо токозахранващо

Rating (VA)	450	650	850	1000	1500	2000
Nominal power (W)	270	380	500	600	900	1200
UPS dimensions WxDxH (mm)	100x292x140			148x315x198		
UPS weight (kg)	4	5	5.5	9	10.5	11.8

Input

Connection type	1 IEC 320-C14
Nominal voltage	230 Vac
Voltage range	160÷290 Vac
Frequency and range	50/60 Hz, 45÷65 Hz

Output

Connection type	1 IEC 320-C13 and 1 Schuko	4 IEC 320-C13 and 1 Schuko
Nominal voltage	230 Vac single phase	
Frequency	50/60 Hz	
Waveform	Simulated sine wave	

Battery

Autonomy time (min) ♦	50% load	8	10	11	13	8	9
	100% load	3	3	3	3	3	3

Connectivity and function extensions

Front panel	LCD, ON/OFF button
Communication	Included: USB. Compatible platforms: Microsoft Windows, Linux, Mac

Environmental

Operating temperature range	0°C ÷ +40°C
Altitude (AMSL)	< 1000 m without power reduction, > 1000 with reduction of 0.5% per 100 m
Audible noise at 1m (dBA)	<40
Relative humidity	0-95%

Standards and certifications

Marking	CE
Safety	IEC/EN 62040-1
EMC	IEC/EN 62040-2
Quality assurance, Environment, Health and Safety	ISO 9001:2008, ISO 14001:2004, BS OHSAS 18001:2007

♦ Measurement conditions: optimised parameters, battery full charged, Power Factor (PF) 0.6