

Заваръчен апарат Деса MMA AC кашон, 1.6-3.2 мм, 140 А, 230 V, Globus 3.0





GLOBUS 3.0



140 Amp; input voltage 1Ph 230 Volt
Continuous setting of welding current,
overload protection



Description

- Code: **204500** Power source + accessories

AC: the output current is alternating

- It allows to weld rutile, stainless steel, etc., electrodes

Features

Welding current range (Amp): 44 - 140A

Open circuit voltage (Volt): 43 - 49V

ELECTRODES :

Rutile: Ø 1,6 - 3,2 mm

1 pH x 230V

Alimentation volt (50/60 Hz): 2,0 - 4,0 KW

Installation Power (Amp): 16A

Cavi diretti - Direct cables

Output connection: 13.9

Dimensions (mm): 390 x 210 x 280

Weight kg ±:

FEATURES: ;

Dimensions (mm): yes

yes

yes

LOGISTIC INFO CODE: 204500

Stepless regulation:

Barcode:

Thermostatic Protection:

390 x 225 x 290

14.5

8011399031706

Package dimension, Wid.-Dep.-Height (mm): 85153913

Package weight kg:

Pieces for pallet:

Продукт: [Заваръчен апарат Deca MMA AC кашон, 1.6-3.2 мм, 140 A, 230 V, Globus 3.0](#)

Категория: [Електродъгово заваряване](#)

Бранд: [Deca](#)

Категория бранд: [Заваръчен апарат Deca](#)