

Апарат Деса заваръчен MIG/MAG с телоподаващо у-во
стомана 0.6-0.8 мм, 145 А, 230 V, D-MIG 350





D-MIG 350



145 Amp; input voltage 1Ph 230 Volt
MIG / NO GAS



Description

- Code: **254400** power source with torch 160A, L = 2m

MIG MAG & NO GAS compact wire feed welder

- NO GAS: with this welding system a special selfshielded wire is used and no gas protection is needed. This system is suggested to obtain high welding penetration. It is ideal for outdoor welding
- MIG MAG
- Primary cable with Schuko plug 2,0m
- Comes complete with:**
- Adapter for refillable bottle

Features

Welding current range (Amp):	35 - 145A
Welding positions (N°):	4
Duty Cycle (Amp) (EN 60974-1 40°C):	115A - 15%
	60A - 60%
	31 - 49V
Open circuit voltage (Volt):	Ø 100 - 200 mm
Wire Suitable Pool:	Ø 0,9 mm
Self shielded wire (mild teel) (Ø mm):	Ø 0,6 - 0,8 mm
	Ø 0,8 mm
Steel wire (Ø mm):	Ø 0,8 - 1,0 mm
Stainless steel wire (Ø mm):	1 Ph x 230V
Aluminium Mg - Si wire (Ø mm):	1,7 KW - 60%
Fuse (Amp):	16A
Alimentation volt (50/60 Hz):	2 rulli - 2 rollers
Wire feeder:	
Installation Power cable:	direct
	direct
	29
	630 x 360 x 490
Torch connection:	

Продукт: [Апарат Деца заваръчен MIG/MAG с телоподаващо у-во стомана 0.6-0.8 мм, 145 A, 230 V, D-MIG 350](#)

Категория: [Електродъгово заваряване](#)

Бранд: [Deca](#)

Категория бранд: [Апарат Деца](#)