




## 1217/1217T



- Valvola compatta in ottone
- Beccuccio Ø 20 mm
- Prolunga curva 8 cm
- Entrata gas raccordo filettato 3/8 sx
- Tubo raccordato 1,5 mt (1217T)

- Soupape compacte en laiton
- Chalumeau avec buse de Ø 20 mm
- Lance courbée de 8 cm
- Filetage entrée 3/8e gauche
- Option tuyau 1.5 m pour le 1217T

- Compact brass valve
- Burner Ø 20 mm
- Bended extension 8 cm
- Gas inlet with 3/8 left threaded fitting
- 1.5 m hose (1217T)

| Art.  |  |  |  |
|-------|---|---|---|
| 1217  | X   | 6   | 360   |
| 1217T | ✓   | 6   | 288   |



|   |  |
|---|--|
|  |  |
| 6   | 288  |

## 1217TRF

- Cannello professionale, dotato di tubo e di regolatore di pressione
- Utilizzabile con gas butano o propano
- Entrata gas: 21,8 x 1,814 sx (attacco bombola Francia)

- Chalumeau professionnel, doté d'un tuyau et d'un détendeur haute pression
- Spécificité: s'adapte au gaz butane ou propane
- Entrée gaz 21,8 x 1,814 sx (pour bouteille française)

- Professional heating torch with hose and regulator
- It can be used with propane or butane gas
- Gas inlet: 21,8 x 1,814 sx (French cylinder connection)






## 1217R/1217RT


- Valvola compatta in ottone
- Beccuccio Ø 17 mm
- Mazza di rame 200g con cuffia antivento asportabile
- Entrata gas raccordo filettato 3/8 sx
- Tubo raccordato 1,5 mt (1217RT)

- Soupape compacte en laiton
- Chalumeau avec buse de Ø 17 mm
- Panne de 200g avec protection anti-vent
- Filetage entrée 3/8e gauche
- Option tuyau 1.5 m pour le 1217RT

- Compact brass valve
- Burner Ø 17 mm
- 200g copper bit with removable windshield cap
- Gas inlet with 3/8 LH threaded fitting
- 1.5 m hose (1217RT)

| Art.   |  |  |  |
|--------|---|---|---|
| 1217R  | X   | 6   | 420   |
| 1217RT | ✓   | 6   | 216   |



| Art.      |  |  |  |
|-----------|---|---|---|
| 1217KITS  | X   | 6   | 300   |
| 1217TKITS | ✓   | 6   | 216   |



## 1217KITS/1217TKITS

- Valvola compatta in ottone
- Beccuccio Ø 17 mm
- Beccuccio a forcella
- Beccuccio a fiamma piatta
- Prolunga curva 8 cm
- Entrata gas raccordo filettato 3/8 sx
- Tubo raccordato 1,5 mt (1217TKITS)

- Soupape compacte en laiton
- Chalumeau avec buse de Ø 17 mm
- Brûleur bec plat
- Brûleur bec en U
- Lance courbée de 8 cm
- Filetage entrée 3/8e gauche
- Option tuyau 1.5 m pour le 1217TKITS

- Compact brass valve
- Fine flame burner (Ø 17 mm)
- Fork burner
- Flat flame burner
- Bended extension 8 cm
- Gas inlet with 3/8 left threaded fitting
- 1.5 m hose (1217TKITS)

