

WELDING INVERTERS



Welding inverter WMEem 200

WMEem 200 is equipped with:

- Compact and portable inverter for MMA welding
- Durable and impact resistance design
- Easy to operate - only current setting needed
- Digital Ampere meter shows the welding current
- Welds most electrodes from \varnothing 1,6 - 5,0 mm
- Capable to work on generator power source
- Over current protection / Over voltage protection
- Automatic hot start
- Automatic arc force
- Automatic anti-stick function

TECHNICAL DATA

| | |
|--|-------------|
| Order No.: | 0302003502 |
| MAIN SUPPLY (V/Ph Hz) | 230V 50HZ |
| Input Voltage Tolerance (%) | ± 15 |
| Input power (kVA) | 9 |
| SETTING RANGE (A) | 20-200 |
| MAX. OUTPUTS AT 15% DUTY CYCLE, A (MMA) | 200 |
| MAX. OUTPUTS AT 60% DUTY CYCLE, A (MMA) | 100 |
| MAX. OUTPUTS AT 100% DUTY CYCLE, A (MMA) | 77 |
| MAX. OUTPUTS AT 15% DUTY CYCLE, A (TIG) | 200 |
| MAX. OUTPUTS AT 60% DUTY CYCLE, A (TIG) | 100 |
| MAX. OUTPUTS AT 100% DUTY CYCLE, A (TIG) | 77 |
| Open-circuit voltage | 82 |
| Maximum current draw (IEFF) | 15 |
| Electrode Sizes Dia. | 1.6-5.0 |
| DIMENSIONS (mm) | 420x154x296 |
| WEIGHT of the machine (kg) | 4.76 |



STANDARD EQUIPMENT:

- welding cable
- return cable

www.rem-power.com

REM POWER SEE, str. 8 Indzikovo No.24, P.O.Box 2, 1040 Skopje, R,M, T: +389 2 3063 180, E: office@rem-power.com