

**Електрожен Деса инверторен MMA DC 1.6-2.5 мм, 80 А, 230 V,
SIL 208**





SIL 208



80 Amp; input voltage 1Ph 230 Volt
Hot Start; Antisticking; Arc Force.



Description

- Code: 279280 power source with cables, welding clamps and carry case

Direct current STICK arc welder, inverter technology.

Features

Welding current range (Amp): 10 - 80A
Duty Cycle (Amp) (DECA use at 20°C): 80A - 50%
Duty Cycle (Amp) (EN 60974-1 40°C): 80A - 7%
Open circuit Voltage (V): 85V
Rutile: Ø 1,6 - 2,5 mm
Basic: _
TIG: _
Alimentation volt (50/60 Hz): 1 Ph x 230V
Fuse (Amp): 2,2 KW
Installation Power (Kw): 16A
Cavi diretti - Direct cables
Output connection: 293 x 132 x 206
Weight (kg): 2.9
Hot start: yes
Dimensions (mm):
Arc force: yes
TIG Scratch: _
Anti-sticking: yes
Generator: +/- 15%
Thermostatic Protection:

Продукт: [Електрожен Деса инверторен MMA DC 1.6-2.5 мм, 80 A, 230 V, SIL 208](#)

Категория: [Електродъгово заваряване](#)

Бранд: [Deca](#)

Категория бранд: [Електрожен Деса](#)