

**Заваръчен апарат Деса MMA AC кашон, 1.6-5 мм, 280 А, 400 V,
T-ARC 530**





T-ARC 530



280 Amp; input voltage 1Ph 230/400
Volt 50/60 Hz
Continuous setting of welding current,
overload protection



Description

- Code: 205500 only power source

AC: the output current is alternating

- It allows to weld rutile, basic (AC), stainless steel, etc., electrodes
- Double open circuit voltage **50 / 70 Volt** to weld with rutile and basic electrodes
- Professional attachments for welding cables

Features

Output selection: 50V / 70V
26 - 280A
Welding current range (Amp) at (50V): 22 - 250A
Welding current range (Amp) at (70V): 50V = (260A - 20%) - (155A - 60%)
70V = (230A - 20%) - (130A - 60%)
Duty Cycle (Amp) (EN 60974-1 40°C): 38 - 77V
Open circuit voltage (Volt):
Rutile: Ø 1,6 - 5,0mm
Basic (AC): Ø 2,0 - 4,0mm
1 Ph x 230/400V
10KW - 60%
Alimentation volt (50/60 Hz):
Fuse (Amp): 32 / 25A
Installation Power (Kw): Dinse 50 mm²
61
Output connection: 780 x 490 x 615
Weight kg:
Fan cooled: yes
Dimensions (mm): yes
50 / 70V: yes
yes
Stepless regulation:

Продукт: [Заваръчен апарат Deca MMA AC кашон, 1.6-5 мм, 280 A, 400 V, T-ARC 530](#)

Категория: [Електродьгово заваряване](#)

Бранд: [Deca](#)

Категория бранд: [Заваръчен апарат Deca](#)